World Journal of Engineering Research and Technology
WJERT
www.wjert.org
SJIF Impact Factor: 7.029

VARIOUS ELECRICAL-AND-THERMOELECTRIC LAWS, RELATIONS, AND COEFFICIENTS IN NEW n(p)-TYPE DEGENERATE "COMPENSATED" CdS(1-x)Te(x) [CdS(1-x)Se(x)]-CRYSTALLINE ALLOYS, ENHANCED BY OUR STATIC DIELECTRIC CONSTANT LAW, ACCURATE FERMI ENERGY, AND ELECRICAL CONDUCTIVITY MODEL (XVII)

Prof. Dr. Huynh Van Cong*

Université de Perpignan Via Domitia, Laboratoire de Mathématiques et Physique (LAMPS), EA 4217, Département de Physique, 52, Avenue Paul Alduy, F-66 860 Perpignan, France.

Article Received on 31/03/2025 **Article Revised on 21/04/2025** **Article Accepted on 11/05/2025**

***Corresponding Author**
Prof. Dr. Huynh Van Cong
Université de Perpignan Via Domitia, Laboratoire de Mathématiques et Physique (LAMPS), EA 4217, Département de Physique, 52, Avenue Paul Alduy, F-66 860 Perpignan, France.

ABSTRACT

In $n^+(p^+) - p(n)$ **X(x)** ≡ **CdS(1-x)Te(x)** [**Y(x)** ≡ **CdS(1-x)Se(x)**]-crystalline alloys, $0 \leq x \leq 1$, taking into account their different values of energy-band-structure parameters, as given in Table 1, and also basing on the same physical model and mathematical treatment method, as used in our recent works[1, 2, 3], various electrical-and-thermoelectric laws, relations, and coefficients, enhanced by our static dielectric constant law given in Equations (1a, 1b), which is due to the effects of the size of donor (acceptor) d(a)-radius $r_{d(a)}$ and the x-concentration, by our accurate Fermi energy, as given in Eq. (11), and finally by our electrical conductivity model, as given in Eq. (14), are now investigated. One notes that, for x=0, their obtained numerical results are reduced to those obtained in the n(p)-type degenerate **CdS-crystal**, in which all the numerical results, obtained in the same physical conditions, are found to be equal, as those observed in Tables 3n(p), 4n(p), 5n(p) and 6n(p), given in Appendix 1. So, some remarkable results can be cited as follows. In Tables 5n(5p), for a given impurity-density N and with increasing temperature T, and then in Tables 6n(6p), for a

given T and with decreasing N, the reduced Fermi-energy $\xi_{n(p)}$ decreases, and other thermoelectric coefficients are in variations, as indicated by the arrows by: (increase: ↗, decrease: ↘). Furthermore, one notes in these Tables that, for any given x, $r_{d(a)}$ and N (or T), with increasing T (or decreasing N) one obtains: (i) for $\xi_{n(p)} = \sqrt{\frac{\pi^2}{3}} \simeq 1.8138$, while the numerical results of the Seebeck coefficient S present a same minimum $(S)_{min.}\left(\simeq -1.563 \times 10^{-4}\frac{V}{K}\right)$, those of the figure of merit ZT show a same maximum $(ZT)_{max.} = 1$, (ii) for $\xi_{n(p)} = 1$, the numerical results of S, ZT, the Mott figure of merit $(ZT)_{Mott}$, the first Van-Cong coefficient VC1, and the Thomson coefficient Ts, present the same results: $-1.322 \times 10^{-4}\frac{V}{K}$, 0.715, 3.290, $1.105 \times 10^{-4}\frac{V}{K}$, and $1.657 \times 10^{-4}\frac{V}{K}$, respectively, and finally (iii) for $\xi_{n(p)} = \sqrt{\frac{\pi^2}{3}} \simeq 1.8138$, $(ZT)_{Mott} = 1$. It seems that these same obtained results could represent **a new law in the thermoelectric properties, obtained in the degenerate case ($\xi_{n(p)} \geq 0$)**.

KEYWORDS: Electrical conductivity, Seebeck coefficient (S), Figure of merit (ZT), First Van-Cong coefficient (VC1), Second Van-Cong coefficient (VC2), Thomson coefficient (Ts), Peltier coefficient (Pt).

INTRODUCTION

In the $\mathbf{n^+(p^+) - p(n)}$ **X(x) ≡ CdS(1-x)Te(x) [Y(x) ≡ CdS(1-x)Se(x)]**- crystalline alloys, $0 \leq x \leq 1$, x being the concentration, the electrical-and-thermoelectric laws, relations, and various coefficients, enhanced by our static dielectric constant law, $\varepsilon(r_{d(a)},x)$, $r_{d(a)}$ being the donor (acceptor) d(a)-radius, given in Equations (1a, 1b), by our accurate Fermi energy, $E_{Fn(Fp)}$, given in Eq. (11), and also by our electrical conductivity model, in Eq. (14), are now investigated, by basing on the same physical model and same mathematical treatment method, as those used in our recent works.[1, 2, 3] It should be noted here that for x=0, these obtained numerical results may be reduced to those given in the n(p)-type degenerate **CdS-crystal**[4, 5, 6-13], in which all the numerical results, obtained in the same physical conditions, are found to be equal, as those observed in Tables 3n(p), 4n(p), 5n(p) and 6n(p), given in Appendix 1. Then, some remarkable results could be noted in the following.

(1) As observed in Equations (3, 5, 6), the critical impurity density $N_{CDn(CDp)}$, defined by the generalized Mott criterium in the metal-insulator transition (**MIT**), is just the density of

electrons (holes), localized in the exponential conduction (valence)-band tail (**EBT**), $N^{EBT}_{CDn(CDp)}$, being obtained with a precision of the order of $\mathbf{2.84\ (2.88)\times 10^{-7}}$, respectively, as given in our recent works.[3] Therefore, the effective electron (hole)-density can be defined as: $N^{*} \equiv N - N_{CDn(CDp)} \simeq N - N^{EBT}_{CDn(CDp)}$, N being the total impurity density, as that observed in the compensated crystals.

(2) The ratio of the inverse effective screening length $k_{sn(sp)}$ to Fermi wave number $k_{Fn(kp)}$ at 0 K, $R_{sn(sp)}(N^{*})$, defined in Eq. (7), is valid at any N^{*}.

(3) The Fermi energy for any N and T, $E_{Fn(Fp)}$, determined in Eq. (11) with a precision of the order of 2.11×10^{-4} [9], affecting all the expressions of electrical-and-thermoelectric coefficients.

(4) Our expressions for the electrical conductivity, σ, and for the Seebeck coefficient, S, determined respectively in Equations (14, 19) are the basic expressions, used to determine all the electrical-and-thermoelectric coefficients.

(5) In Tables 5n(5p) given Appendix 1, for a given impurity density N and with increasing temperature T, and further in Tables 6n(6p) given Appendix 1, for a given T and with decreasing N, the reduced Fermi-energy $\xi_{n(p)}$ decreases, giving rise to the variations of various thermoelectric coefficients, as indicated by the arrows by: (increase: ↗, decrease: ↘). Furthermore, one notes in these Tables that, for any given x, $r_{d(a)}$ and N (or T), with increasing T (or decreasing N), one obtains: (i) for $\xi_{n(p)} = \sqrt{\frac{\pi^2}{3}} \simeq 1.8138$, while the numerical results of the Seebeck coefficient S present a same minimum $(S)_{min.}\left(\simeq -1.563\times 10^{-4}\frac{V}{K}\right)$, those of the figure of merit ZT show a same maxi**mum** $(ZT)_{max.} = 1$, (ii) for $\xi_{n(p)} = 1$, the numerical results of S, ZT, the Mott figure of merit $(ZT)_{Mott}$, the first Van-Cong coefficient VC1, and the Thomson coefficient Ts, present the same results: $-1.322\times 10^{-4}\frac{V}{K}$, 0.715, 3.290, $1.105\times 10^{-4}\frac{V}{K}$, and $1.657\times 10^{-4}\frac{V}{K}$, respectively, and finally (iii) for $\xi_{n(p)} = \sqrt{\frac{\pi^2}{3}} \simeq 1.8138$, $(ZT)_{Mott} = 1$. It seems that these same results could represent **a new law in the thermoelectric properties, obtained in the degenerate case ($\xi_{n(p)} \geq 0$)**.

OUR STATIC DIELECTRIC CONSTANT LAW AND GENERALIZED MOTT CRITERIUM IN THE METAL-INSULATOR TRANSITION

First of all, in $\mathbf{n^+(p^+)-p(n)\ X(x)\equiv CdS(1\text{-}x)Te(x)}$ $\mathbf{[\ Y(x)\equiv CdS(1\text{-}x)Se(x)]}$- crystalline alloys at T=0 K, we denote the donor (acceptor) d(a)-radius by $r_{d(a)}$, the corresponding intrinsic one by: $\mathbf{r_{do(ao)}=r_{Ge(Ge)}[r_{Si(Si)}]}$, the effective averaged numbers of equivalent conduction (valence)-bands by : $g_{c(v)}$, the unperturbed relative effective electron (hole) mass in conduction (valence) bands by: $m_{c(v)}(x)/m_o$, m_o being the free electron mass, the unperturbed relative static dielectric constant by: $\varepsilon_o(x)$, and the intrinsic band gap by: $E_{go}(x)$. Then, their values are reported in Table 1 in Appendix 1.

Therefore, we can define the effective donor (acceptor)-ionization energy in absolute values as:

$E_{do(ao)}(x)=\frac{13600\times[m_{c(v)}(x)/m_o]}{[\varepsilon_o(x)]^2}$ meV , and then, the isothermal bulk modulus, by: $B_{do(ao)}(x)\equiv\frac{E_{do(ao)}(x)}{\left(\frac{4\pi}{s}\right)\times\left(r_{do(ao)}\right)^s}$.

Our Static Dielectric Constant Law

Here, the changes in all the energy-band-structure parameters, expressed in terms of the effective relative dielectric constant $\varepsilon(r_{d(a)},x)$, developed as follows.

At $r_{d(a)}=r_{do(ao)}$, the needed boundary conditions are found to be, for the impurity-atom volume $V=(4\pi/3)\times\left(r_{d(a)}\right)^3$, $V_{do(ao)}=(4\pi/3)\times\left(r_{do(ao)}\right)^3$, for the pressure p, $p_o=0$, and for the deformation potential energy (or the strain energy) α, $\alpha_o=0$. Further, the two important equations, used to determine the α -variation, $\Delta\alpha\equiv\alpha-\alpha_o=\alpha$, are defined by: $\frac{dp}{dV}=-\frac{B}{V}$ and $p=-\frac{d\alpha}{dV}$, giving rise to : $\frac{d}{dV}\left(\frac{d\alpha}{dV}\right)=\frac{B}{V}$. Then, by an integration, one gets:

$$[\Delta\alpha(r_{d(a)},x)]_{n(p)}=B_{do(ao)}(x)\times(V-V_{do(ao)})\times\ln\left(\frac{V}{V_{do(ao)}}\right)=E_{do(ao)}(x)\times\left[\left(\frac{r_{d(a)}}{r_{do(ao)}}\right)^3-1\right]\times\ln\left(\frac{r_{d(a)}}{r_{do(ao)}}\right)^3\geq 0.$$

Furthermore, we also showed that, as $r_{d(a)}>r_{do(ao)}$ $(r_{d(a)}<r_{do(ao)})$, the compression (dilatation) gives rise to the increase (the decrease) in the energy gap $E_{gn(gp)}(r_{d(a)},x)$, and the effective donor (acceptor)-ionization energy $E_{d(a)}(r_{d(a)},x)$ in absolute values, obtained in the effective Bohr model, which is represented respectively by : $\pm[\Delta\alpha(r_{d(a)},x)]_{n(p)}$,

$$E_{gno(gpo)}(r_{d(a)},x)-E_{go}(x)=E_{d(a)}(r_{d(a)},x)-E_{do(ao)}(x)=E_{do(ao)}(x)\times\left[\left(\frac{\varepsilon_o(x)}{\varepsilon(r_{d(a)})}\right)^2-1\right]=+[\Delta\alpha(r_{d(a)},x)]_{n(p)},$$

for $r_{d(a)} \geq r_{do(ao)}$, and for $r_{d(a)} \leq r_{do(ao)}$,

$$E_{gno(gpo)}(r_{d(a)},x) - E_{go}(x) = E_{d(a)}(r_{d(a)},x) - E_{do(ao)}(x) = E_{do(ao)}(x) \times \left[\left(\frac{\varepsilon_o(x)}{\varepsilon(r_{d(a)})}\right)^2 - 1\right] = -\left[\Delta\alpha(r_{d(a)},x)\right]_{n(p)}.$$

Therefore, one obtains the expressions for relative dielectric constant $\varepsilon(r_{d(a)},x)$ and energy band gap $E_{gn(gp)}(r_{d(a)},x)$, as :

(i)-for $r_{d(a)} \geq r_{do(ao)}$, since $\varepsilon(r_{d(a)},x) = \frac{\varepsilon_o(x)}{\sqrt{1+\left[\left(\frac{r_{d(a)}}{r_{do(ao)}}\right)^3 - 1\right]\times \ln\left(\frac{r_{d(a)}}{r_{do(ao)}}\right)^3}} \leq \varepsilon_o(x)$, being a **new** $\boldsymbol{\varepsilon(r_{d(a)},x)}$**-law**,

$$E_{gno(gpo)}(r_{d(a)},x) - E_{go}(x) = E_{d(a)}(r_{d(a)},x) - E_{do(ao)}(x) = E_{do(ao)}(x) \times \left[\left(\frac{r_{d(a)}}{r_{do(ao)}}\right)^3 - 1\right] \times \ln\left(\frac{r_{d(a)}}{r_{do(ao)}}\right)^3 \geq 0, \quad (1a)$$

According to the increase in both $E_{gn(gp)}(r_{d(a)},x)$ and $E_{d(a)}(r_{d(a)},x)$, with increasing $r_{d(a)}$ and for a given x, and

(ii)-for $r_{d(a)} \leq r_{do(ao)}$, since $\varepsilon(r_{d(a)},x) = \frac{\varepsilon_o(x)}{\sqrt{1-\left[\left(\frac{r_{d(a)}}{r_{do(ao)}}\right)^3 - 1\right]\times \ln\left(\frac{r_{d(a)}}{r_{do(ao)}}\right)^3}} \geq \varepsilon_o(x)$, with a condition, given by: $\left[\left(\frac{r_{d(a)}}{r_{do(ao)}}\right)^3 - 1\right] \times \ln\left(\frac{r_{d(a)}}{r_{do(ao)}}\right)^3 < 1$, being a **new** $\boldsymbol{\varepsilon(r_{d(a)},x)}$**-law**,

$$E_{gno(gpo)}(r_{d(a)},x) - E_{go}(x) = E_{d(a)}(r_{d(a)},x) - E_{do(ao)}(x) = -E_{do(ao)}(x) \times \left[\left(\frac{r_{d(a)}}{r_{do(ao)}}\right)^3 - 1\right] \times \ln\left(\frac{r_{d(a)}}{r_{do(ao)}}\right)^3 \leq 0, \quad (1b)$$

corresponding to the decrease in both $E_{gno(gpo)}(r_{d(a)},x)$ and $E_{d(a)}(r_{d(a)},x)$, with decreasing $r_{d(a)}$ and for a given x.

It should be noted that, in the following, all the electrical-and-thermoelectric properties strongly depend on this **new** $\boldsymbol{\varepsilon(r_{d(a)},x)}$**-law.**

Furthermore, the effective Bohr radius $a_{Bn(Bp)}(r_{d(a)},x)$ is defined by:

$$a_{Bn(Bp)}(r_{d(a)},x) \equiv \frac{\varepsilon(r_{d(a)},x)\times\hbar^2}{m_{c(v)}(x)\times m_o \times q^2} = 0.53\times 10^{-8}\ \text{cm} \times \frac{\varepsilon(r_{d(a)},x)}{m_{c(v)}(x)}. \quad (2)$$

Generalized Mott Criterium in the MIT

Now, it is interesting to remark that the critical total donor (acceptor)-density in the MIT at T=0 K, $N_{CDn(NDp)}(r_{d(a)},x)$, was given by the Mott's criterium, with an empirical parameter, $M_{n(p)}$, as [2, 3]:

$$N_{CDn(CDp)}(r_{d(a)},x)^{1/3} \times a_{Bn(Bp)}(r_{d(a)},x) = M_{n(p)},\ M_{n(p)} = 0.25, \quad (3)$$

depending thus on our **new $\varepsilon(r_{d(a)},x)$-law**.

This excellent one can be explained from the definition of the reduced effective Wigner-Seitz (**WS**) radius $r_{sn(sp),M}$, in the Mott's criterium, being characteristic of interactions, by :

$$r_{sn(sp),M}(N, r_{d(a)}, x) \equiv \left(\frac{3}{4\pi N}\right)^{1/3} \times \frac{1}{a_{Bn(Bp)}(r_{d(a)},x)} = 1.1723 \times 10^{8} \times \left(\frac{1}{N}\right)^{1/3} \times \frac{m_{c(v)}(x) \times m_0}{\varepsilon(r_{d(a)},x)}, \quad (4)$$

being equal to, in particular, at $N=N_{CDn(CDp)}(r_{d(a)},x)$: $r_{sn(sp),M}(N_{CDn(CDp)}(r_{d(a)},x), r_{d(a)},x)=$ **2.4813963**, for any $(r_{d(a)},x)$-values.

Then, from Eq. (4), one also has :

$$N_{CDn(CDp)}(r_{d(a)},x)^{1/3} \times a_{Bn(Bp)}(r_{d(a)},x) = \left(\frac{3}{4\pi}\right)^{\frac{1}{3}} \times \frac{1}{2.4813963} = 0.25 = (WS)_{n(p)} = M_{n(p)}, \quad (5)$$

explaining thus the existence of the Mott's criterium.

Furthermore, by using $M_{n(p)} = 0.25$, according to the empirical Heisenberg parameter $\mathcal{H}_{n(p)} = 0.47137$, as those given in our previous work[3], we have also showed that $N_{CDn(CDp)}$ is just **the density of electrons (holes) localized in the exponential conduction (valence)-band tail**, $N^{EBT}_{CDn(CDp)}$, with a precision of the order of $2.84\ (2.88) \times 10^{-7}$, respectively .[3]

It shoud be noted that the values of $M_{n(p)}$ and $\mathcal{H}_{n(p)}$ could be chosen so that those of $N_{CDn(CDp)}$ and $N^{EBT}_{CDn(CDp)}$ are found to be in good agreement with their experimental results.

Therefore, the density of electrons (holes) given in parabolic conduction (valence) bands can be defined, as that given in compensated materials:

$N^{*}(N, r_{d(a)},x) \equiv N - N_{CDn(NDp)}(r_{d(a)},x) = N^{*}$, for a presentation simplicity. (6)

In summary, as observed in Tables 7 and 8 of our previous paper[3], one remarks that, for a given x and an increasing $r_{d(a)}$, $\varepsilon(r_{d(a)},x)$ decreases, while $E_{gno(gpo)}(r_{d(a)},x)$, $N_{CDn(NDp)}(r_{d(a)},x)$ and $N^{EBT}_{CDn(CDp)}(r_{d(a)},x)$ increase, affecting strongly all electrical-and-thermoelectric properties, as those observed in following Sections.

PHYSICAL MODEL

In $n^+(p^+)-p(n)\,\mathbf{X(x)}\,\mathbf{[Y(x)]}$- crystalline alloys, if denoting the Fermi wave number by: $k_{Fn(Fp)}(N^*)\equiv\left(\frac{3\pi^2N^*}{g_{c(v)}}\right)^{\frac{1}{3}}$, where the $g_{c(v)}$-values are given in Table 1 in Appendix 1, the reduced effective Wigner-Seitz (**WS**) radius $r_{sn(sp)}$, characteristic of interactions, being given in Eq. (4), in which N is replaced by N^*, is now defined by:

$\gamma\times r_{sn(sp)}(N^*)\equiv\frac{k_{Fn(Fp)}^{-1}}{a_{Bn(Bp)}}<1$, $r_{sn(sp)}\left(N,r_{d(a)},x\right)\equiv\left(\frac{3g_{c(v)}}{4\pi N^*}\right)^{1/3}\times\frac{1}{a_{Bn(Bp)}(r_{d(a)},x)}$, being proportional to $N^{*-1/3}$. Here, $\gamma=(4/9\pi)^{1/3}$, $k_{Fn(Fp)}^{-1}$ means the averaged distance between ionized donors (acceptors), and $a_{Bn(Bp)}(r_{d(a)},x)$ is determined in Eq. (2).

Then, the ratio of the inverse effective screening length $k_{sn(sp)}$ to Fermi wave number $k_{Fn(kp)}$ at 0 K is defined by:

$$R_{sn(sp)}(N^*)\equiv\frac{k_{sn(sp)}}{k_{Fn(Fp)}}=\frac{k_{Fn(Fp)}^{-1}}{k_{sn(sp)}^{-1}}=R_{snWS(spWS)}+\left[R_{snTF(spTF)}-R_{snWS(spWS)}\right]e^{-r_{sn(sp)}}<1, \quad (7)$$

being valid at any N^*.

Here, these ratios, $R_{snTF(spTF)}$ and $R_{snWS(spWS)}$, can be determined as follows.

First, for $N\gg N_{CDn(NDp)}(r_{d(a)},x)$, according to the **Thomas-Fermi (TF)-approximation**, the ratio $R_{snTF(spTF)}(N^*)$ is reduced to

$$R_{snTF(spTF)}(N^*)\equiv\frac{k_{snTF(spTF)}}{k_{Fn(Fp)}}=\frac{k_{Fn(Fp)}^{-1}}{k_{snTF(spTF)}^{-1}}=\sqrt{\frac{4\gamma r_{sn(sp)}}{\pi}}\ll 1, \quad (8)$$

being proportional to $N^{*-1/6}$.

Secondly, for $N\ll N_{CDn(NDp)}(r_{d(a)})$, according to the **Wigner-Seitz (WS)-approximation**, the ratio $R_{snWS(snWS)}$ is respectively reduced to

$$R_{sn(sp)WS}(N^*)\equiv\frac{k_{sn(sp)WS}}{k_{Fn}}=0.5\times\left(\frac{s}{2\pi}-\gamma\frac{d\left[r_{sn(sp)}^2\times E_{CE}(N^*)\right]}{dr_{sn(sp)}}\right), \quad (9)$$

Where $E_{CE}(N^*)$ is the majority-carrier correlation energy (CE), being determined by:

$$E_{CE}(N^*)=\frac{-0.87553}{0.0908+r_{sn(sp)}}+\frac{\frac{0.87553}{0.0908+r_{sn(sp)}}+\left(\frac{2[1-\ln(2)]}{\pi^2}\right)\times\ln(r_{sn(sp)})-0.093288}{1+0.0384728\times r_{sn(sp)}^{1.67378876}}.$$

Furthermore, in the highly degenerate case, the physical conditions are found to be given by:

$$\frac{k_{Fn(Fp)}^{-1}}{a_{Bn(Bp)}}<\frac{\eta_{n(p)}}{E_{Fno(Fpo)}}\equiv\frac{1}{A_{n(p)}}<\frac{k_{Fn(Fp)}^{-1}}{k_{sn(sp)}^{-1}}\equiv R_{sn(sp)}<1,\ \eta_{n(p)}(N^*)\equiv\frac{\sqrt{2\pi\times\left(\frac{N^*}{g_{c(v)}}\right)}}{\varepsilon(r_{d(a)})}\times q^2k_{sn(sp)}^{-1/2}, \quad (10)$$

Which gives: $A_{n(p)}(N^*) = \frac{E_{Fno(Fpo)}(N^*)}{\eta_{n(p)}(N^*)}$, $E_{Fno(Fpo)}(N^*) \equiv \frac{\hbar^2 \times k^2_{Fn(Fp)}(N^*)}{2 \times m_{c(v)}(x) \times m_0}$.

FERMI ENERGY AND FERMI-DIRAC DISTRIBUTION FUNCTION

Fermi Energy

Here, for a presentation simplicity, we change all the sign of various parameters, given in the $p^+ - X(x)$- crystalline alloy in order to obtain the same one, as given in the $n^+ - X(x)$- crystalline alloy, according to the reduced Fermi energy $E_{Fn(Fp)}$, $\xi_{n(p)}(N, r_{d(a)}, x, T) \equiv \frac{E_{Fn(Fp)}(N, r_{d(a)}, x, T)}{k_B T} > 0 (< 0)$, obtained respectively in the degenerate (non-degenerate) case.

For any $(N, r_{d(a)}, x, T)$, the reduced Fermi energy $\xi_{n(p)}(N, r_{d(a)}, x, T)$ or the Fermi energy $E_{Fn(Fp)}(N, r_{d(a)}, x, T)$, obtained in our previous paper[9], obtained with a precision of the order of 2.11×10^{-4}, is found to be given by:

$$\xi_{n(p)}(u) \equiv \frac{E_{Fn(Fp)}(u)}{k_B T} = \frac{G(u) + Au^B F(u)}{1 + Au^B} \equiv \frac{V(u)}{W(u)}, A = 0.0005372 \text{ and } B = 4.82842262, \quad (11)$$

where u is the reduced electron density, $u(N, r_{d(a)}, x, T) \equiv \frac{N^*}{N_{c(v)}(T,x)}$, $N_{c(v)}(T,x) = 2g_{c(v)} \times \left(\frac{m_{c(v)}(x) \times m_0 \times k_B T}{2\pi\hbar^2}\right)^{\frac{3}{2}} (cm^{-3})$, $F(u) = au^{\frac{2}{3}}\left(1 + bu^{-\frac{4}{3}} + cu^{-\frac{8}{3}}\right)^{-\frac{2}{3}}$, $a = \left[3\sqrt{\pi}/4\right]^{2/3}$, $b = \frac{1}{8}\left(\frac{\pi}{3}\right)^2$, $c = \frac{62.3739855}{1920}\left(\frac{\pi}{3}\right)^4$, and $G(u) \simeq Ln(u) + 2^{-\frac{3}{2}} \times u \times e^{-du}$; $d = 2^{3/2}\left[\frac{1}{\sqrt{27}} - \frac{3}{16}\right] > 0$.

So, in the non-degenerate case ($u \ll 1$), one has: $E_{Fn(Fp)}(u) = k_B T \times G(u) \simeq k_B T \times Ln(u)$ as **$u \longrightarrow 0$, the limiting non-degenerate condition**, and in the very degenerate case ($u \gg 1$), one gets: $E_{Fn(Fp)}(u \gg 1) = k_B T \times F(u) = k_B T \times au^{\frac{2}{3}}\left(1 + bu^{-\frac{4}{3}} + cu^{-\frac{8}{3}}\right)^{-\frac{2}{3}} \simeq \frac{\hbar^2 \times k^2_{Fn(Fp)}(N^*)}{2 \times m_{c(v)}(x) \times m_0}$ as **$u \longrightarrow \infty$, the limiting degenerate condition**. In other words, $\xi_{n(p)} \equiv \frac{E_{Fn(Fp)}}{k_B T}$ is accurate, and it also verifies the correct limiting conditions.

In particular, at T=0K, since $u^{-1} = 0$, Eq. (11) is reduced to: $E_{Fno(Fpo)}(N^*) \equiv \frac{\hbar^2 \times k^2_{Fn(Fp)}(N^*)}{2 \times m_{c(v)}(x) \times m_0}$, being proportional to $(N^*)^{2/3}$, and also equal to 0 at $N^* = 0$, according to the MIT.

In the following, it should be noted that all the electrical-and-thermoelectric properties strongly depend on such the accurate expression of $\xi_{n(p)}(N, r_{d(a)}, x, T)$.[9]

Fermi-Dirac Distribution Function (FDDF)

The Fermi-Dirac distribution function (FDDF) is given by: $f(E) \equiv (1+e^{\gamma})^{-1}$, $\gamma \equiv (E - E_{Fn(Fp)})/(k_B T)$.

So, the average of E^p, calculated using the FDDF-method, as developed in our previous works [1, 6] is found to be given by:

$\langle E^p \rangle_{FDDF} \equiv G_p(E_{Fn(Fp)}) \times E^p_{Fn(Fp)} \equiv \int_{-\infty}^{\infty} E^p \times \left(-\frac{\partial f}{\partial E}\right) dE, \quad -\frac{\partial f}{\partial E} = \frac{1}{k_B T} \times \frac{e^{\gamma}}{(1+e^{\gamma})^2}.$

Further, one notes that, at 0 K, $-\frac{\partial f}{\partial E} = \delta(E - E_{Fno(Fpo)})$, $\delta(E - E_{Fno(Fpo)})$ being the Dirac delta (δ)-function. Therefore, $G_p(E_{Fno(Fpo)}) = 1$.

Then, at low T, by a variable change $\gamma \equiv (E - E_{Fn(Fp)})/(k_B T)$, one has:

$G_p(E_{Fn(Fp)}) \equiv 1 + E^{-p}_{Fn(Fp)} \times \int_{-\infty}^{\infty} \frac{e^{\gamma}}{(1+e^{\gamma})^2} \times (k_B T\gamma + E_{Fn(Fp)})^p d\gamma = 1 + \sum_{\mu=1,2,\ldots}^{p} C_p^{\beta} \times (k_B T)^{\beta} \times E^{-\beta}_{Fn(Fp)} \times I_{\beta}$,

where $C_p^{\beta} \equiv p(p-1)\ldots(p-\beta+1)/\beta!$ and the integral I_{β} is given by:

$I_{\beta} = \int_{-\infty}^{\infty} \frac{\gamma^{\beta} \times e^{\gamma}}{(1+e^{\gamma})^2} d\gamma = \int_{-\infty}^{\infty} \frac{\gamma^{\beta}}{(e^{\gamma/2}+e^{-\gamma/2})^2} d\gamma$, vanishing for old values of β. Then, for even values of $\beta = 2n$, with n=1, 2, …, one obtains:

$I_{2n} = 2\int_0^{\infty} \frac{\gamma^{2n} \times e^{\gamma}}{(1+e^{\gamma})^2} d\gamma$.

Now, using an identity $(1+e^{\gamma})^{-2} \equiv \sum_{s=1}^{\infty} (-1)^{s+1} s \times e^{\gamma(s-1)}$, a variable change: $s\gamma = -t$, the Gamma function: $\int_0^{\infty} t^{2n} e^{-t} dt \equiv \Gamma(2n+1) = (2n)!$, and also the definition of the Riemann's zeta function: $\zeta(2n) \equiv 2^{2n-1}\pi^{2n}|B_{2n}|/(2n)!$, B_{2n} being the Bernoulli numbers, one finally gets: $I_{2n} = (2^{2n}-2) \times \pi^{2n} \times |B_{2n}|$. So, from above Eq. of $\langle E^p \rangle_{FDDF}$, we get in the degenerate case the following ratio:

$G_p(E_{Fn(Fp)}) \equiv \frac{\langle E^p \rangle_{FDDF}}{E^p_{Fn(Fp)}} = 1 + \sum_{n=1}^{p} \frac{p(p-1)\ldots(p-2n+1)}{(2n)!} \times (2^{2n}-2) \times |B_{2n}| \times y^{2n} \equiv G_{p\geq 1}(y),$ (12)

Where $y \equiv \frac{\pi}{\xi_{n(p)}(N^*,T)} = \frac{\pi k_B T}{E_{Fn(Fp)}(N^*,T)}$.

Then, some usual results of $G_{p\geq 1}(y)$ are given in Table 2 in Appendix 1, being needed to determine all the following electrical-and-thermoelectric properties.

ELECTRICAL-AND-THERMOELECTRIC PROPERTIES

Here, if denoting, for majority electrons (holes), the electrical conductivity by $\sigma(N, r_{d(a)}, x, T)$ expressed in $\mathrm{ohm}^{-1} \times \mathrm{cm}^{-1}$, the thermal conductivity by $\kappa(N, r_{d(a)}, x, T)$ in $\frac{W}{cm \times K}$, and the Lorenz number L defined by: $L = \frac{\pi^2}{3} \times \left(\frac{k_B}{q}\right)^2 = 2.4429637 \left(\frac{W \times ohm}{K^2}\right) = 2.4429637 \times 10^{-8} (V^2 \times K^{-2})$, then the well-known Wiedemann-Frank law states that the ratio, $\frac{\kappa}{\sigma}$, is proportional to the temperature T(K), as:

$$\frac{\kappa(N, r_{d(a)}, x, T)}{\sigma(N, r_{d(a)}, x, T)} = L \times T. \quad (13)$$

We now determine the general form of σ in the following.

First of all, it is expressed in terms of the kinetic energy of the electron (hole), $E_k \equiv \frac{\hbar^2 \times k^2}{2 \times m_{c(v)}(x) \times m_o}$, or the wave number k, as:

$$\sigma(k) \equiv \frac{q^2 \times k}{\pi \times \hbar} \times \frac{k}{k_{sn(sp)}} \times \left[k \times a_{Bn(Bp)}\right] \times \left(\frac{E_k}{\eta_{n(p)}}\right)^{1/2},$$

Which is thus proportional to $E_k{}^2$.

Then, for $\underline{E \geq 0}$, we obtain: $\langle E^2 \rangle_{FDDF} \equiv G_2\left(y = \frac{\pi k_B T}{E_{Fn(Fp)}}\right) \times E^2_{Fn(Fp)}$, and $G_2(y) = \left(1 + \frac{y^2}{3}\right) \equiv G_2(N, r_{d(a)}, x, T)$, with $y \equiv \frac{\pi}{\xi_{n(p)}}$, $\xi_{n(p)} = \xi_{n(p)}(N, r_{d(a)}, x, T)$ for a presentation simplicity. Therefore, one obtains[1]:

$$\sigma(N, r_{d(a)}, x, T) \equiv \left[\frac{q^2}{\pi \times \hbar} \times \frac{k_{Fn(Fp)}(N^*)}{R_{sn\,(sp)}(N^*)} \times \left[k_{Fn(Fp)}(N^*) \times a_{Bn(Bp)}(r_{d(a)})\right] \times \sqrt{A_{n(p)}(N^*)}\right] \times \left[G_2(N, r_{d(a)}, x, T) \times \left(\frac{E_{Fn(Fp)}(N, r_{d(a)}, x, T)}{E_{Fno\,(Fpo)}(N^*)}\right)^2\right] \left(\frac{1}{ohm \times cm}\right),$$

$$\frac{q^2}{\pi \times \hbar} = 7.7480735 \times 10^{-5}\ \mathrm{ohm}^{-1},\ A_{n(p)}(N^*) = \frac{E_{Fno(Fpo)}(N^*)}{\eta_{n(p)}(N^*)},\ R_{sn(sp)}(N^*) \equiv \frac{k_{sn(sp)}}{k_{Fn(Fp)}}, \quad (14)$$

Which can be used to define the resistivity as: $\rho(N, r_{d(a)}, x, T) \equiv 1/\sigma(N, r_{d(a)}, x, T)$, noting again that $N^* \equiv N - N_{CDn(NDp)}(r_{d(a)}, x)$. This $\sigma(N, r_{d(a)}, x, T)$-result is an essential one in this paper, being used to determine other electrical-and-thermoelectric properties.

In Eq. (14), one notes that at T= 0 K, $\sigma(N, r_{d(a)}, x, T = 0K)$ is proportional to $E^2_{Fno(Fpo)}$, or to $(N^*)^{\frac{4}{3}}$. Thus, $\sigma(N = N_{CDn(NDp)}, r_{d(a)}, x, T = 0K) = 0$ at $N^* = 0$, at which the metal-insulator transition (MIT) occurs.

Electrical Coefficients

The relaxation time τ is related to σ by[1]:

$\tau(N, r_{d(a)}, x, T) \equiv \sigma(N, r_{d(a)}, x, T) \times \frac{m_{c(v)}(x) \times m_o}{q^2 \times (N^*/g_{c(v)})}$. Therefore, the mobility μ is given by:

$$\mu(N, r_{d(a)}, x, T) \equiv \mu(N^*, r_{d(a)}, T) = \frac{q \times \tau(N, r_{d(a)} x T)}{m_{c(v)}(x) \times m_o} = \frac{\sigma(N, r_{d(a)} x T)}{q \times (N^*/g_{c(v)})} \left(\frac{cm^2}{V \times s}\right). \quad (15)$$

Here, at T= 0K, $\mu(N^*, r_{d(a)}, T)$ is thus proportional to $(N^*)^{1/3}$, since $\sigma(N^*, r_{d(a)}, T = 0K)$ is proportional to $(N^*)^{4/3}$. Thus, $\mu(N^* = 0, r_{d(a)}, T = 0K) = 0$ at $N^* = 0$, at which the metal-insulator transition (MIT) occurs.

Then, since τ and σ are both proportional to $E_{Fn(Fp)}(N^*, T)^2$, as given above, the Hall factor is defined by:

$r_H(N, r_{d(a)}, x, T) \equiv \frac{\langle \tau^2 \rangle_{FDDF}}{[\langle \tau \rangle_{FDDF}]^2} = \frac{G_4(y)}{[G_2(y)]^2}$, $y \equiv \frac{\pi}{\xi_{n(p)}(N, r_{d(a)} x T)} = \frac{\pi k_B T}{E_{Fn(Fp)}(N, r_{d(a)} x T)}$, and therefore, the Hall mobility yields:

$$\mu_H(N, r_{d(a)}, x, T) \equiv \mu(N, r_{d(a)}, x, T) \times r_H(N^*, T) \left(\frac{cm^2}{V \times s}\right), \quad (16)$$

Noting that, at T=0K, since $r_H(N, r_{d(a)}, x, T) = 1$, one then gets: $\mu_H(N, r_{d(a)}, x, T) \equiv \mu(N, r_{d(a)}, x, T)$.

Our generalized Einstein relation

Our generalized Einstein relation is found to be defined as [1]:

$$\frac{D(N, r_{d(a)} x T)}{\mu(N, r_{d(a)} x T)} \equiv \frac{N^*}{q} \times \frac{dE_{Fn(Fp)}}{dN^*} \equiv \frac{k_B \times T}{q} \times \left(u \frac{d\xi_{n(p)}(u)}{du}\right) = \sqrt{\frac{3 \times L}{\pi^2}} \times T \times \left(u \frac{d\xi_{n(p)}(u)}{du}\right), \frac{k_B}{q} = \sqrt{\frac{3 \times L}{\pi^2}} \quad (17)$$

Where $D(N, r_{d(a)}, x, T)$ is the diffusion coefficient, $\xi_{n(p)}(u)$ is defined in Eq. (11), and the mobility $\mu(N, r_{d(a)}, x, T)$ is determined in Eq. (15). Then, by differentiating this function $\xi_{n(p)}(u)$ with respect to u, one thus obtains $\frac{d\xi_{n(p)}(u)}{du}$. Therefore, Eq. (17) can also be rewritten as:

$\frac{D(N, r_{d(a)} x T)}{\mu(N, r_{d(a)} x T)} = \frac{k_B \times T}{q} \times u \frac{V'(u) \times W(u) - V(u) \times W'(u)}{W^2(u)}$, where $W'(u) = ABu^{B-1}$ and $V'(u) = u^{-1} + 2^{-\frac{s}{2}} e^{-du}(1 - du) + \frac{2}{s} Au^{B-1} F(u) \left[\left(1 + \frac{sB}{2}\right) + \frac{4}{s} \times \frac{bu^{-\frac{4}{s}} + 2cu^{-\frac{8}{s}}}{1 + bu^{-\frac{4}{s}} + cu^{-\frac{8}{s}}}\right]$. One remarks that: (i) as $u \to 0$, one has: $W^2 \simeq 1$ and $u[V' \times W - V \times W'] \simeq 1$, and therefore: $\frac{D_{n(p)}(u)}{\mu} \simeq \frac{k_B \times T}{q}$, and (ii) as $u \to \infty$, one has: $W^2 \approx A^2 u^{2B}$ and $u[V' \times W - V \times W'] \approx \frac{2}{s} a u^{2/3} A^2 u^{2B}$, and therefore, in this **highly degenerate case** and at T=0K, the **above generalized Einstein relation** is reduced to

the **usual Einstein one**: $\frac{D(N,r_{d(a)},x,T=0\,K)}{\mu(N,r_{d(a)},x,T=0\,K)} \approx \frac{2}{3}E_{Fno(Fpo)}(N^*)/q$. In other words, **Eq. (17) verifies the correct limiting conditions**.

Furthermore, in the present degenerate case ($u \gg 1$), Eq. (17) gives:

$$\frac{D(N,r_{d(a)},x,T)}{\mu(N,r_{d(a)},x,T)} \simeq \frac{2}{3}\times\frac{E_{Fno(Fpo)}(u)}{q}\times\left[1+\frac{4}{3}\times\frac{\left(bu^{-\frac{4}{s}}+2cu^{-\frac{s}{s}}\right)}{\left(1+bu^{-\frac{4}{s}}+cu^{-\frac{s}{s}}\right)}\right], \quad (18)$$

where $a=\left[3\sqrt{\pi}/4\right]^{2/3}$, $b=\frac{1}{8}\left(\frac{\pi}{s}\right)^2$ and $c=\frac{62.3739855}{1920}\left(\frac{\pi}{s}\right)^4$.

In Tables 3n(3p) given in Appendix 1, for given x, $N > N_{CDn(CDp)}$ and T(=4.5 K and 77 K), and from Equations (14, 15, 16, 17), the numerical results of the coefficients: σ, μ, μ_H and D are found to be decreased with increasing $r_{d(a)}$, respectively.

Thermoelectric Coefficients

First of all, from Eq. (14), obtained for $\sigma(N, r_{d(a)}, x, T)$, the well-known Mott definition for the thermoelectric power or for the Seebeck coefficient, S, is found to be given by:

$$S(N, r_{d(a)}, x, T) \equiv \frac{-\pi^2}{3}\times\frac{k_B}{q>0}\times k_B T\times\frac{\partial \ln\sigma(E)}{\partial E}\Big]_{E=E_{Fn(Fp)}} = \frac{-\pi^2}{3}\times\frac{k_B}{q}\times\frac{\partial \ln\sigma\left(\xi_{n(p)}\right)}{\partial \xi_{n(p)}}.$$

Then, using Eq. (11), for the degenerate case, $\xi_{n(p)} \geq 0$, one gets, by putting

$$F_S(N, r_{d(a)}, x, T) \equiv \left[1-\frac{y^2}{3\times G_2\left(y=\frac{\pi}{\xi_{n(p)}}\right)}\right],$$

$$S(N, r_{d(a)}, x, T) \equiv \frac{-\pi^2}{3}\times\frac{k_B}{q}\times\frac{2F_{Sb}(N^*,T)}{\xi_{n(p)}} = -\sqrt{\frac{3\times L}{\pi^2}}\times\frac{2\times\xi_{n(p)}}{\left(1+\frac{3\times\xi_{n(p)}^2}{\pi^2}\right)} = -2\sqrt{L}\times\frac{\sqrt{(ZT)_{Mott}}}{1+(ZT)_{Mott}}\left(\frac{V}{K}\right) < 0, \quad (ZT)_{Mott} = \frac{\pi^2}{3\times\xi_{n(p)}^2}, \quad (19)$$

according to:

$$\frac{\partial S}{\partial \xi_{n(p)}} = \sqrt{\frac{3\times L}{\pi^2}}\times 2\times\frac{\frac{3\times\xi_{n(p)}^2}{\pi^2}-1}{\left(1+\frac{3\times\xi_{n(p)}^2}{\pi^2}\right)^2} = \sqrt{\frac{3\times L}{\pi^2}}\times 2\times\frac{(ZT)_{Mott}\times[1-(ZT)_{Mott}]}{[1+(ZT)_{Mott}]^2}.$$

Here, one notes that: (i) as $\xi_{n(p)} \to +\infty$ or $\xi_{n(p)} \to +0$, one has a same limiting value of S: $S \to -0$,

(ii) at $\xi_{n(p)} = \sqrt{\frac{\pi^2}{3}} \simeq 1.8138$, since $\frac{\partial S}{\partial \xi_{n(p)}} = 0$, one therefore gets: a minimum $(S)_{min.} = -\sqrt{L} \simeq -1.563 \times 10^{-4} \left(\frac{V}{K}\right)$, and

(iii) at $\xi_{n(p)} = 1$ one obtains: $S \simeq -1.322 \times 10^{-4} \left(\frac{V}{K}\right)$.

Further, the figure of merit, ZT, is found to be defined by:

$$ZT\left(N, r_{d(a)}, x, T\right) \equiv \frac{S^2 \times \sigma \times T}{\kappa} = \frac{S^2}{L} = \frac{4 \times (ZT)_{Mott}}{[1+(ZT)_{Mott}]^2}. \quad (20)$$

Here, one notes that: (i) $\frac{\partial (ZT)}{\partial \xi_{n(p)}} = 2 \times \frac{S}{L} \times \frac{\partial S}{\partial \xi_{n(p)}}$, $S < 0$, (ii) at $\xi_{n(p)} = \sqrt{\frac{\pi^2}{3}} \simeq 1.8138$, since $\frac{\partial (ZT)}{\partial \xi_{n(p)}} = 0$, one gets: a maximum $(ZT)_{max.} = 1$,and $(ZT)_{Mott} = 1$, and (iii) at $\xi_{n(p)} = 1$, one obtains: $ZT \simeq 0.715$ and $(ZT)_{Mott} = \frac{\pi^2}{3} \simeq 3.290$.

Finally, the first Van-Cong coefficient, VC1, can be defined by:

$$VC1\left(N, r_{d(a)}, x, T\right) \equiv -N^* \times \frac{dS}{dN^*} \left(\frac{V}{K}\right) = N^* \times \frac{\partial S}{\partial \xi_{n(p)}} \times -\frac{\partial \xi_{n(p)}}{\partial N^*}, \text{ being equal to 0 for } \xi_{n(p)} = \sqrt{\frac{\pi^2}{3}}, \quad (21)$$

and the second Van-Cong coefficient, VC2, as:

$$VC2\left(N, r_{d(a)}, x, T\right) \equiv T \times VC1\ (V), \quad (22)$$

the Thomson coefficient, Ts, by:

$$Ts\left(N, r_{d(a)}, x, T\right) \equiv T \times \frac{dS}{dT} \left(\frac{V}{K}\right) = T \times \frac{\partial S}{\partial \xi_{n(p)}} \times \frac{\partial \xi_{n(p)}}{\partial T}, \text{ being equal to 0 for } \xi_{n(p)} = \sqrt{\frac{\pi^2}{3}}, \quad (23)$$

and the Peltier coefficient, Pt, as:

$$Pt\left(N, r_{d(a)}, x, T\right) \equiv T \times S\ (V). \quad (24)$$

One notes here that in next Tables 5n(p) and 6n(p) given in Appendix 1, obtained with such given physical conditions N (or T) for the decreasing $\xi_{n(p)}$, since $VC1\left(N, r_{d(a)}, x, T\right)$ and $Ts\left(N, r_{d(a)}, x, T\right)$ are expressed in terms of $\frac{-dS}{dN^*}$ and $\frac{dS}{dT}$, one has: $[VC1, Ts] < 0$ for $\xi_{n(p)} > \sqrt{\frac{\pi^2}{3}}$, $[VC1, Ts] = 0$ for $\xi_{n(p)} = \sqrt{\frac{\pi^2}{3}}$, and $[VC1, Ts] > 0$ for $\xi_{n(p)} < \sqrt{\frac{\pi^2}{3}}$, stating also that for $\xi_{n(p)} = \sqrt{\frac{\pi^2}{3}}$:

(i) S, determined in Eq. (19), thus presents **a same minimum** $(S)_{min.} = -\sqrt{L} \simeq -1.563 \times 10^{-4} \left(\frac{V}{K}\right)$,

(ii) ZT, determined in Eq. (20), therefore presents **a same maximum:** $(ZT)_{max.} = 1$, since the variations of ZT are expressed in terms of $[VC1, Ts] \times S, \quad S < 0$.

Furthermore, it is interesting to remark that the (VC2)-coefficient is related to our generalized Einstein relation (17) by:

$$\frac{k_B}{q} \times VC2\left(N, r_{d(a)}, x, T\right) \equiv -\frac{\delta S}{\delta \xi_{n(p)}} \times \frac{D\left(N, r_{d(a)}, x T\right)}{\mu\left(N, r_{d(a)}, x T\right)} \left(\frac{V^2}{K}\right), \qquad \frac{k_B}{q} = \sqrt{\frac{3 \times L}{\pi^2}}, \tag{25}$$

According, in this work, with the use of our Eq. (21), to:

$$VC2\left(N, r_{d(a)}, x, T\right) \equiv -\frac{D\left(N, r_{d(a)}, x, T\right)}{\mu\left(N, r_{d(a)}, x, T\right)} \times 2 \times \frac{(ZT)_{Mott} \times [1-(ZT)_{Mott}]}{[1+(ZT)_{Mott}]^2} \ (V).$$

Of course, our relation (25) is reduced to: $\frac{D}{\mu}$, VC1 and VC2, being determined respectively by Equations (17, 21, 22).

Now, in the degenerate n(p)-type $X(x) -$ alloy, and for N> $N_{CDn(CDp)}$, and for T=3K (80K), the numerical results of various thermoelectric coefficients are reported in Tables 4n(4p) in Appendix 1, noting that their variations with increasing $r_{d(a)}$ are represented by the arrows: ↗ (increase), and ↘ (decrease), respectively.

Then, in Tables 5n(5p) given Appendix 1 for a given **N** and with increasing T, and in Tables 6n(6p) given Appendix 1 for a given **T** and with decreasing N, the reduced Fermi-energy $\xi_{n(p)}$ decreases, and various thermoelectric coefficients are in variations, as indicated by the arrows as: (increase: ↗, decrease: ↘).

CONCLUDING REMARKS

Here, some concluding remarks are given as follows.

(1) In $n^+(p^+) - p(n)\, X(x)[Y(x)]$ - crystalline alloys, $0 \leq x \leq 1$, the electrical-and-thermoelectric laws, relations, and various coefficients are found to be enhanced by our static dielectric constant law, $\varepsilon(r_{d(a)}, x)$, being, for a given x, decreased with increasing $r_{d(a)}$, as that given in Tables 7 and 8 of our recent work[3], by our accurate Fermi energy, $E_{Fn(Fp)}$, being given in Eq. (11), and in particular by our electrical conductivity model, being given in Eq. (14).

(2) The generalized Mott criterium in the MIT is expressed in Equations (3, 5, 6), stating that the critical impurity density $N_{CDn(CDp)}$ is just the density of electrons (holes), localized in the exponential conduction (valence)-band tail, $N^{EBT}_{CDn(CDp)}$, obtained with a precision of the order of $2.84\,(2.88)\times10^{-7}$, respectively, as those given in Tables 7 and 8 of our previous work[3], and the effective electron (hole)-density can be defined by: $N^{*}\equiv N-N_{CDn(CDp)}\simeq N-N^{EBT}_{CDn(CDp)}$, as that observed in the compensated crystals. This should be **a new result**.

(3) The ratio of the inverse effective screening length $k_{sn(sp)}$ to Fermi wave number $k_{Fn(kp)}$ at 0 K, $R_{sn(sp)}(N^{*})$, defined in Eq. (7), is valid for any density N^{*}. This should be **a new result**.

(4) In Tables 5n(5p) given Appendix 1, for a given impurity density N and with increasing temperature T, and then in Tables 6n(6p) given Appendix 1, for a given T and with decreasing N, the reduced Fermi-energy $\xi_{n(p)}$ decreases, and other thermoelectric coefficients are in variations, as indicated by the arrows by: (increase: ↗, decrease: ↘). One remarks in these Tables that, for any given x, $r_{d(a)}$ and N (or T), with increasing T (or decreasing N), one obtains: (i) for $\xi_{n(p)}=\sqrt{\frac{\pi^2}{3}}\simeq1.8138$, while the numerical results of the Seebeck coefficient S present a **same minimum** $(S)_{min.}=-\sqrt{L}\simeq-1.563\times10^{-4}\left(\frac{V}{K}\right)$, those of the figure of merit ZT show a **same maximum** $(ZT)_{max}=1$, (ii) for $\xi_{n(p)}=1$, the numerical results of S, ZT, the Mott figure of merit $(ZT)_{Mott}$, the Van-Cong coefficient VC1, and the Thomson coefficient Ts, present the same results: $-1.322\times10^{-4}\frac{V}{K}$, **0.715, 3.290,** $1.105\times10^{-4}\frac{V}{K}$, **and** $1.657\times10^{-4}\frac{V}{K}$, respectively, and finally (iii) for $\xi_{n(p)}=\sqrt{\frac{\pi^2}{3}}\simeq1.8138$, $(ZT)_{Mott}=1$. It seems that these same results could represent **a new law in the thermoelectric properties, obtained in the degenerate case**.

(5) Finally, our electrical-and-thermoelectric relation is given in Eq. (25) by:

$\frac{k_B}{q}\times VC2\left(N,r_{d(a)},x,T\right)\equiv-\frac{\delta S}{\delta\xi_{n(p)}}\times\frac{D\left(N,r_{d(a)},x,T\right)}{\mu\left(N,r_{d(a)},x,T\right)}\left(\frac{V^2}{K}\right)$, $\frac{k_B}{q}=\sqrt{\frac{3\times L}{\pi^2}}$, according, in this work, to:

$VC2\left(N,r_{d(a)},x,T\right)\equiv-\frac{D\left(N,r_{d(a)},x,T\right)}{\mu\left(N,r_{d(a)},x,T\right)}\times2\times\frac{(ZT)_{Mott}\times[1-(ZT)_{Mott}]}{[1+(ZT)_{Mott}]^2}$ (V), being reduced to: $\frac{D}{\mu}$, VC1 and VC2, determined respectively in Equations (17, 21, 22). This should be **a new result**.

REFERENCES

1. Van Cong H. Various Electrical-and-Thermoelectric Laws, Relations, and Coefficients in New n(p)-type Degenerate "Compensated" GaAs(1-x)P(x)-Crystalline Alloy, Enhanced by Our Static Dielectric Constant Law and Electrical Conductivity Model (XI). WJERT, 2025; 11(4): 207-238.
2. Van Cong H. 48.3 % (50.1 %)-Highest Efficiencies in CdS(1-x)Te(x) Crystalline Alloy Junction Solar Cells at 300 K, According to Highest Hot Reservoir Temperatures, 580.3 K (601.2 K), obtained from Carnot-Efficiency Theorem (XI). WJERT, 2024; 10(6): 175-193.
3. Van Cong, H. New Critical Impurity Density in Metal-Insulator Transition, obtained in Various n(p)-Type Degenerate Crystalline Alloys, being Just That of Carriers Localized in Exponential Band Tails. WJERT, 2024; 10(4): 05-23.
4. Van Cong H. Same maximum figure of merit ZT(=1), due to the effect of impurity size, obtained in the n(p)-type degenerate Ge-crystal ($\xi_{n(p)} \geq \mathbf{1}$), at same reduced Fermi energy $\xi_{n(p)} = \sqrt{\frac{\pi^2}{3}} \simeq 1.8138$, same minimum Seebeck coefficient $(S)_{min.}\left(\simeq -1.563 \times 10^{-4}\frac{V}{K}\right)$, same maximum $(ZT)_{max.} = 1$, and same $(ZT)_{Mott}\left(=\frac{\pi^2}{3\xi_{n(p)}^2} = 1\right)$, SCIREA Journal of Physics. 2023; 8(4): 407-430.
5. Van Cong, H. Same Maximal Figure of Merit ZT(=1), Due to the Effect of Impurity Size, Obtained in the n(p)-Type Degenerate Si-Crystal ($\xi_{n(p)} \geq 1$), at Same Reduced Fermi Energy $\xi_{n(p)}(= 1.8138)$ and Same Minimum Seebeck Coefficient $S\left(= -1.563 \times 10^{-4}\frac{V}{K}\right)$, at which Same $(ZT)_{Mott}\left(=\frac{\pi^2}{3\xi_{n(p)}^2} = 1\right)$. SCIREA Journal of Physics, 2023; 8(2): 66-90.
6. Van Cong, H. Effects of donor size and heavy doping on optical, electrical and thermoelectric properties of various degenerate donor-silicon systems at low temperatures. American Journal of Modern Physics, 2018; 7(4): 136-165.
7. Kim, H. S. et al. Characterization of Lorenz number with Seebeck coefficient measurement. APL Materials, 2015; 3(4): 041506.
8. Hyun, B. D. et al. Electrical-and-Thermoelectric Properties of $90\%Bi_2Te_3 - 5\%Sb_2Te_3 - 5\%Sb_2Se_3$ Single Crystals Doped with SbI_3. Scripta Materialia, 1998; 40(1): 49-56.
9. Van Cong, H. and Debiais, G. A simple accurate expression of the reduced Fermi energy for any reduced carrier density. J. Appl. Phys., 1993; 73: 1545-1546.

10. Van Cong, H. et al. Size effect on different impurity levels in semiconductors. Solid State Communications, 1984; 49: 697-699.
11. Van Cong, H. Diffusion coefficient in degenerate semiconductors. Phys. Stat. Sol. (b), 1984; 101: K27.
12. Van Cong, H. and Doan Khanh, B. Simple accurate general expression of the Fermi-Dirac integral $F_j(a)$ and for j> -1. Solid-State Electron., 1992; 35(7): 949-951.
13. Van Cong, H. New series representation of Fermi-Dirac integral $F_j(-\infty < a < \infty)$ for arbitrary j> -1, and its effect on $F_j(a \geq 0_+)$ for integer $j \geq 0$. Solid-State Electron., 1991; 34(5): 489-492.

APPENDIX 1

Table 1: In these X(x)-and-Y(x) crystalline alloys, their different values of energy-band-structure parameters, for a given x, are given in the following.

In the $\mathbf{X(x) \equiv CdS_{1-x}Te_x}$ **-crystalline alloy**, in which $r_{do(ao)} = r_{S(Cd)}$ =**0.104** nm (**0.148** nm), we have[2, 3]: $g_{c(v)}(x) = 1(1) \times x + 1(1) \times (1-x)$, $m_{c(v)}(x)/m_o = 0.095\ (0.82) \times x + 0.197\ (0.801) \times (1-x)$, $\varepsilon_o(x) = 10.31 \times x + 9 \times (1-x)$, $E_{go}(x) = 1.62 \times x + 2.58 \times (1-x)$.

In the $\mathbf{Y(x) \equiv CdS_{1-x}Se_x}$ **-crystalline alloy**, in which $r_{do(ao)} = r_{S(Cd)}$ =**0.104** nm (**0.148** nm), we have [2]: $g_{c(v)}(x) = 1(1) \times x + 1(1) \times (1-x)$, $m_{c(v)}(x)/m_o = 0.11\ (0.45) \times x + 0.197\ (0.801) \times (1-x)$, $\varepsilon_o(x) = 10.2 \times x + 9 \times (1-x)$, $E_{go}(x) = 1.84 \times x + 2.58 \times (1-x)$.

Table 2: Expressions for $G_{p\geq 1}(y \equiv \frac{\pi}{\xi_{n(p)}})$, due to the Fermi-Dirac distribution function, noting that $G_{p=1}(y \equiv \frac{\pi k_B T}{E_{Fn(Fp)}} = \frac{\pi}{\xi_{n(p)}}) = 1$, used to determine the electrical-and-thermoelectric coefficients.

$G_{3/2}(y)$	$G_2(y)$	$G_{5/2}(y)$	$G_3(y)$	$G_{7/2}(y)$	$G_4(y)$	$G_{9/2}(y)$
$\left(1+\frac{y^2}{8}+\frac{7y^4}{640}\right)$	$\left(1+\frac{y^2}{3}\right)$	$\left(1+\frac{5y^2}{8}-\frac{7y^4}{384}\right)$	$(1+y^2)$	$\left(1+\frac{35y^2}{24}+\frac{49y^4}{384}\right)$	$\left(1+2y^2+\frac{7y^4}{15}\right)$	$\left(1+\frac{21y^2}{8}+\frac{147y^4}{128}\right)$

Table 3n

In the $\mathbf{X(x) \equiv CdS_{1-x}Te_x}$**-crystalline alloy**, one notes that, for given x, $N > 2N_{CDn}$ and T(=4.5 K and 77 K), the functions: σ, μ, μ_H, D, expressed respectively in $\left(\frac{10^3}{ohm \times cm}, \frac{10^3 \times cm^2}{V \times s}, \frac{10^3 \times cm^2}{V \times s}, \frac{10^2 \times cm^2}{s}\right)$, decrease with increasing r_d.

Donor	P	As	Sb	Sn
r_d (nm) ↗	0.110	0.118	0.136	0.140
For x=**0**, the values of (σ, μ, μ_H, D) at **4.5 K**				
N (10^{19} cm^{-3})				
4	5.76, 0.926, 0.926, 1.31	5.18, 0.838, 0.838, 1.18	3.38, 0.571, 0.571, 0.78	3.02, 0.521, 0.521, 0.70
6	8.21, 0.871, 0.871, 1.62	7.38, 0.786, 0.786, 1.46	4.82, 0.528, 0.528, 0.96	4.32, 0.479, 0.479, 0.87
10	12.9, 0.813, 0.813, 2.14	11.5, 0.732, 0.732, 1.93	7.51, 0.484, 0.484, 1.26	6.74, 0.437, 0.437, 1.13
For x=**0.5**, the values of (σ, μ, μ_H, D) at **4.5 K**				
N (10^{19} cm^{-3})				
4	10.5, 1.662, 1.662, 3.21	9.47, 1.495, 1.495, 2.89	6.14, 0.984, 0.984, 1.88	5.51, 0.887, 0.887, 1.69
6	15.1, 1.585, 1.585, 4.03	13.6, 1.423, 1.423, 3.61	8.76, 0.927, 0.927, 2.34	7.85, 0.834, 0.834, 2.10
10	24.0, 1.502, 1.502, 5.37	21.4, 1.345, 1.345, 4.81	13.7, 0.867, 0.867, 3.09	12.3, 0.777, 0.777, 2.76
For x=**1**, the values of (σ, μ, μ_H, D) at **4.5 K**				
N (10^{19} cm^{-3})				
4	24.5, 3.831, 3.831, 11.4	21.9, 3.423, 3.423, 10.2	13.9, 2.184, 2.184, 6.51	12.4, 1.952, 1.952, 5.81
6	35.5, 3.700, 3.700, 14.5	31.7, 3.301, 3.301, 12.9	20.0, 2.093, 2.093, 8.18	17.9, 1.867, 1.867, 7.30
10	56.9, 3.553, 3.553, 19.6	50.7, 3.166, 3.166, 17.4	31.8, 1.993, 1.993, 11.0	28.3, 1.774, 1.774, 9.76
For **x=0**, the values of (σ, μ, μ_H, D) at **77 K**				
N (10^{19} cm^{-3})				
4	5.79, 0.931, 0.943, 1.31	5.21, 0.843, 0.854, 1.19	3.40, 0.575, 0.583, 0.78	3.04, 0.524, 0.532, 0.71
6	8.24, 0.874, 0.880, 1.63	7.41, 0.789, 0.795, 1.47	4.83, 0.530, 0.534, 0.97	4.33, 0.481, 0.485, 0.87
10	12.9, 0.814, 0.817, 2.14	11.6, 0.733, 0.735, 1.93	7.53, 0.485, 0.487, 1.26	6.75, 0.438, 0.439, 1.13

For **x=0.5**, the values of (σ, μ, μ_H, D) at **77 K**

N (10^{19} cm^{-3})			
4	10.6, 1.667, 1.678, 3.22	9.50, 1.499, 1.510, 2.89	6.16, 0.987, 0.994, 1.89	5.52, 0.890, 0.896, 1.69
6	15.2, 1.586, 1.594, 4.03	13.6, 1.425, 1.431, 3.61	8.77, 0.930, 0.932, 2.34	7.86, 0.835, 0.838, 2.10
10	24.0, 1.503, 1.506, 5.37	21.5, 1.346, 1.348, 4.81	13.7, 0.867, 0.869, 3.09	12.3, 0.778, 0.779, 2.76

For **x=1**, the values of (σ, μ, μ_H, D) at **77 K**

N (10^{19} cm^{-3})			
4	24.5, 3.836, 3.847, 11.4	21.9, 3.428, 3.437, 10.2	13.9, 2.187, 2.193, 6.52	12.4, 1.954, 1.960, 5.82
6	35.5, 3.703, 3.709, 14.5	31.7, 3.304, 3.309, 12.9	20.0, 2.094, 2.098, 8.19	17.9, 1.868, 1.871, 7.30
10	56.9, 3.554, 3.557, 19.6	50.7, 3.167, 3.170, 17.4	31.9, 1.994, 1.995, 11.0	28.3, 1.775, 1.776, 9.76

In the $\mathbf{Y(x) \equiv CdS_{1-x}Se_x - alloy}$, one notes that, for given x, $N > N_{CDn}$ and T(=4.5 K and 77 K), the functions: σ, μ, μ_H, D, expressed respectively in $\left(\frac{10^8}{ohm \times cm}, \frac{10^8 \times cm^2}{V \times s}, \frac{10^8 \times cm^2}{V \times s}, \frac{10^2 \times cm^2}{s}\right)$, decrease with increasing r_d.

Donor		P	As	Sb	Sn
r_d (nm)	↗	0.110	0.118	0.136	0.140

For x=**0**, the values of (σ, μ, μ_H, D) at **4.5 K**

N (10^{19} cm^{-3})			
4	5.76, 0.926, 0.926, 1.31	5.18, 0.838, 0.838, 1.18	3.38, 0.571, 0.571, 0.78	3.02, 0.521, 0.521, 0.70
6	8.21, 0.871, 0.871, 1.62	7.38, 0.786, 0.786, 1.46	4.82, 0.528, 0.528, 0.96	4.32, 0.479, 0.479, 0.87
10	12.9, 0.813, 0.813, 2.14	11.5, 0.732, 0.732, 1.93	7.51, 0.484, 0.484, 1.26	6.74, 0.437, 0.437, 1.13

For x=**0.5**, the values of (σ, μ, μ_H, D) at **4.5 K**

N (10^{19} cm^{-3})			
4	9.62, 1.518, 1.518, 2.79	8.64, 1.366, 1.366, 2.51	5.61, 0.903, 0.903, 1.64	5.03, 0.816, 0.816, 1.47
6	13.8, 1.445, 1.445, 3.49	12.4, 1.298, 1.298, 3.13	8.00, 0.849, 0.849, 2.03	7.17, 0.764, 0.764, 1.82
10	21.8, 1.366, 1.366, 4.65	19.5, 1.224, 1.224, 4.16	12.5, 0.792, 0.792, 2.68	11.2, 0.710, 0.710, 2.40

For x=**1**, the values of (σ, μ, μ_H, D) at **4.5 K**

N (10^{19} cm^{-3})			
4	18.7, 2.924, 2.924, 7.54	16.7, 2.617, 2.617, 6.74	10.7, 1.684, 1.684, 4.32	9.55, 1.508, 1.508, 3.87
6	27.0, 2.814, 2.814, 9.51	24.1, 2.515, 2.515, 8.50	15.3, 1.606, 1.606, 5.42	13.7, 1.436, 1.436, 4.84
10	43.1, 2.692, 2.692, 12.8	38.4, 2.402, 2.402, 11.4	24.3, 1.522, 1.522, 7.23	21.6, 1.357, 1.357, 6.44

For **x=0**, the values of (σ, μ, μ_H, D) at **77 K**

N (10^{19} cm^{-3})			
4	5.79, 0.931, 0.943, 1.31	5.21, 0.843, 0.854, 1.19	3.40, 0.575, 0.583, 0.78	3.04, 0.524, 0.532, 0.71
6	8.24, 0.874, 0.880, 1.63	7.41, 0.789, 0.795, 1.47	4.83, 0.530, 0.534, 0.97	4.33, 0.481, 0.485, 0.87
10	12.9, 0.814, 0.817, 2.14	11.6, 0.733, 0.735, 1.93	7.53, 0.485, 0.487, 1.26	6.75, 0.438, 0.439, 1.13

For **x=0.5**, the values of (σ, μ, μ_H, D) at **77 K**

N (10^{19} cm^{-3})			
4	9.65, 1.523, 1.534, 2.80	8.67, 1.371, 1.381, 2.51	5.63, 0.906, 0.913, 1.64	5.05, 0.818, 0.825, 1.48
6	13.8, 1.448, 1.454, 3.49	12.4, 1.300, 1.306, 3.13	8.01, 0.851, 0.854, 2.03	7.18, 0.766, 0.769, 1.83
10	21.8, 1.367, 1.370, 4.65	19.5, 1.225, 1.228, 4.16	12.5, 0.792, 0.794, 2.68	11.2, 0.711, 0.713, 2.40

For **x=1**, the values of (σ, μ, μ_H, D) at **77 K**

N (10^{19} cm^{-3})				
4	18.7, 2.929, 2.940, 7.55	16.7, 2.621, 2.632, 6.75	10.7, 1.687, 1.693, 4.33	9.57, 1.511, 1.517, 3.87
6	27.0, 2.817, 2.823, 9.52	24.1, 2.517, 2.523, 8.51	15.4, 1.608, 1.611, 5.42	13.7, 1.437, 1.440, 4.84
10	43.1, 2.694, 2.697, 12.8	38.4, 2.403, 2.406, 11.4	24.3, 1.523, 1.524, 7.23	21.6, 1.358, 1.359, 6.44

Table 3p

In the $\mathbf{X(x) \equiv CdS_{1-x}Te_x}$**-crystalline alloy**, one notes that, for given x, $N > 2N_{CDp}$ and T(=4.5 K and 77 K), the functions: σ, μ, μ_H, D, expressed respectively in $\left(\frac{10^8}{ohm \times cm}, \frac{10^2 \times cm^2}{V \times s}, \frac{10^2 \times cm^2}{V \times s}, \frac{cm^2}{s}\right)$, decrease with increasing r_a.

Acceptor		Ga	Mg	In	Cd
r_a (nm)	↗	0.126	0.140	0.144	0.148

For x=**0**, the values of (σ, μ, μ_H, D) at **4.5 K**

N (10^{19} cm^{-3})				
15	1.96, 1.279, 1.280, 8.11	1.51, 1.193, 1.194, 6.66	1.46, 1.186, 1.186, 6.50	1.44, 1.184, 1.184, 6.44
16	2.11, 1.250, 1.250, 8.47	1.65, 1.160, 1.160, 7.00	1.60, 1.152, 1.152, 6.85	1.58, 1.150, 1.150, 6.80
17	2.26, 1.223, 1.224, 8.81	1.79, 1.131, 1.131, 7.34	1.74, 1.123, 1.123, 7.18	1.72, 1.120, 1.120, 7.13

For x=**0.5**, the values of (σ, μ, μ_H, D) at **4.5 K**

N (10^{19} cm^{-3})				
15	2.26, 1.352, 1.352, 8.98	1.80, 1.246, 1.346, 7.52	1.75, 1.236, 1.237, 7.36	1.74, 1.233, 1.234, 7.31
16	2.42, 1.324, 1.324, 9.35	1.95, 1.216, 1.216, 7.87	1.90, 1.205, 1.206, 7.71	1.89, 1.202, 1.202, 7.66
17	2.58, 1.298, 1.298, 9.70	2.10, 1.889, 1.889, 8.20	2.05, 1.178, 1.178, 8.04	2.03, 1.175, 1.175, 7.89

For x=**1**, the values of (σ, μ, μ_H, D) at **4.5 K**

N (10^{19} cm^{-3})				
15	2.54, 1.430, 1.430, 9.79	2.08, 1.307, 1.307, 8.30	2.03, 1.295, 1.295, 8.14	2.01, 1.291, 1.291, 8.09
16	2.72, 1.402, 1.402, 10.2	2.23, 1.278, 1.278, 8.65	2.18, 1.266, 1.266, 8.49	2.17, 1.262, 1.262, 8.44
17	2.89, 1.377, 1.377, 10.5	2.39, 1.252, 1.252, 8.99	2.34, 1.240, 1.240, 8.82	2.32, 1.236, 1.236, 8.77

For x=**0**, the values of (σ, μ, μ_H, D) at **77K**

N (10^{19} cm^{-3})				
15	2.01, 1.315, 1.397, 8.29	1.56, 1.237, 1.335, 6.84	1.51, 1.231, 1.332, 6.69	1.50, 1.229, 1.331, 6.63
16	2.16, 1.280, 1.350, 8.63	1.70, 1.196, 1.277, 7.18	1.65, 1.189, 1.273, 7.02	1.63, 1.187, 1.271, 6.97
17	2.31, 1.250, 1.311, 8.96	1.84, 1.162, 1.231, 7.49	1.79, 1.154, 1.224, 7.33	1.77, 1.151, 1.222, 7.28

For x=**0.5**, the values of (σ, μ, μ_H, D) at **77K**

N (10^{19} cm^{-3})				
15	2.32, 1.387, 1.465, 9.16	1.86, 1.285, 1.373, 7.70	1.81, 1.276, 1.365, 7.54	1.79, 1.273, 1.363, 7.49
16	2.48, 1.353, 1.422, 9.51	2.00, 1.248, 1.323, 8.03	1.95, 1.239, 1.314, 7.87	1.94, 1.236, 1.312, 7.82
17	2.64, 1.324, 1.384, 9.85	2.15, 1.217, 1.281, 8.35	2.10, 1.207, 1.272, 8.19	2.08, 1.204, 1.269, 8.14

For x=**1**, the values of (σ, μ, μ_H, D) at **77K**

15	2.61, 1.464, 1.542, 9.98	2.13, 1.343, 1.426, 8.48	2.08, 1.332, 1.416, 8.32	2.07, 1.328, 1.413, 8.27
16	2.78, 1.432, 1.500, 10.3	2.29, 1.309, 1.381, 8.82	2.24, 1.297, 1.370, 8.66	2.22, 1.294, 1.366, 8.60
17	2.95, 1.403, 1.464, 10.7	2.44, 1.279, 1.342, 9.14	2.39, 1.267, 1.330, 8.98	2.37, 1.263, 1.326, 8.92

In the $\mathbf{Y(x) \equiv CdS_{1-x}Se_x - alloy}$, one notes that, for given x, $N > N_{CDp}$ and T(=4.5 K and 77 K), the functions: σ, μ, μ_H, D, expressed respectively in $\left(\frac{10^3}{ohm \times cm}, \frac{10^2 \times cm^2}{V \times s}, \frac{10^2 \times cm^2}{V \times s}, \frac{cm^2}{s}\right)$, decrease with increasing r_a.

Acceptor		Ga	Mg	In	Cd
r_a (nm)	↗	0.126	0.140	0.144	0.148

For x=**0**, the values of (σ, μ, μ_H, D) at **4.5 K**

N (10^{19} cm^{-3})				
15	1.96, 1.279, 1.280, 8.11	1.51, 1.193, 1.194, 6.66	1.46, 1.186, 1.186, 6.50	1.44, 1.184, 1.184, 6.44
16	2.11, 1.250, 1.250, 8.47	1.65, 1.160, 1.160, 7.00	1.60, 1.152, 1.152, 6.85	1.58, 1.150, 1.150, 6.80
17	2.26, 1.223, 1.224, 8.81	1.79, 1.131, 1.131, 7.34	1.74, 1.123, 1.123, 7.18	1.72, 1.120, 1.120, 7.13

For x=**0.5**, the values of (σ, μ, μ_H, D) at **4.5 K**

N (10^{19} cm^{-3})				
15	3.72, 1.808, 1.808, 17.9	3.17, 1.620, 1.620, 15.5	3.11, 1.601, 1.601, 15.2	3.09, 1.595, 1.595, 15.1
16	3.95, 1.780, 1.780, 18.5	3.37, 1.592, 1.592, 16.0	3.31, 1.574, 1.574, 15.8	3.29, 1.568, 1.568, 15.7
17	4.18, 1.754, 1.754, 19.1	3.57, 1.567, 1.567, 16.6	3.50, 1.549, 1.549, 16.3	3.48, 1.543, 1.543, 16.2

For x=**1**, the values of (σ, μ, μ_H, D) at **4.5 K**

N (10^{19} cm^{-3})				
15	7.11, 3.095, 3.095, 45.8	6.15, 2.718, 2.718, 39.8	6.06, 2.681, 2.681, 39.2	6.03, 2.668, 2.668, 39.0
16	7.52, 3.060, 3.060, 47.3	6.51, 2.686, 2.686, 41.2	6.41, 2.648, 2.648, 40.6	6.38, 2.636, 2.636, 40.4
17	7.93, 3.029, 3.029, 48.9	6.86, 2.656, 2.656, 42.5	6.76, 2.619, 2.619, 41.9	6.72, 2.606, 2.606, 41.6

For x=**0**, the values of (σ, μ, μ_H, D) at **77K**

N (10^{19} cm^{-3})				
15	2.01, 1.315, 1.397, 8.29	1.56, 1.237, 1.335, 6.84	1.51, 1.231, 1.332, 6.69	1.50, 1.229, 1.331, 6.63
16	2.16, 1.280, 1.350, 8.63	1.70, 1.196, 1.277, 7.18	1.65, 1.189, 1.273, 7.02	1.63, 1.187, 1.271, 6.97
17	2.31, 1.250, 1.311, 8.96	1.84, 1.162, 1.231, 7.49	1.79, 1.154, 1.224, 7.33	1.77, 1.151, 1.222, 7.28

For x=**0.5**, the values of (σ, μ, μ_H, D) at **77K**

N (10^{19} cm^{-3})				
15	3.77, 1.828, 1.876, 18.0	3.21, 1.640, 1.685, 15.6	3.15, 1.621, 1.667, 15.4	3.13, 1.615, 1.660, 15.3
16	3.99, 1.798, 1.840, 18.7	3.41, 1.610, 1.650, 16.2	3.35, 1.591, 1.631, 15.9	3.33, 1.585, 1.625, 15.8
17	4.22, 1.771, 1.809, 19.3	3.60, 1.583, 1.619, 16.7	3.54, 1.564, 1.600, 16.4	3.52, 1.558, 1.594, 16.3

For x=**1**, the values of (σ, μ, μ_H, D) at **77K**

N (10^{19} cm^{-3})				
15	7.14, 3.111, 3.147, 46.0	6.19, 2.732, 2.765, 40.0	6.09, 2.695, 2.727, 39.4	6.06, 2.682, 2.714, 39.2
16	7.55, 3.075, 3.107, 47.5	6.54, 2.698, 2.728, 41.3	6.44, 2.661, 2.690, 40.7	6.41, 2.649, 2.677, 40.5
17	7.96, 3.042, 3.072, 49.0	6.89, 2.668, 2.694, 42.6	6.79, 2.630, 2.657, 42.0	6.75, 2.618, 2.644, 41.8

Table 4n

In the $\mathbf{X(x) \equiv CdS_{1-x}Te_x}$ **-crystalline alloy** and for T=3K and 80K, the numerical results of various thermoelectric coefficients are reported. Further, their variations with increasing $r_{d(a)}$ are represented by the arrows: ↗ (increase), and ↘ (decrease).

Donor		P	As	Sb	Sn
For **x=0** and **N=5 × 10^{18} cm^{-3}**, one has:					
$\xi_{n(T=3K)}$	↘	175.787	168.118	109.771	80.924

$\xi_{n(T=80K)}$	↘	6.786	6.507	4.339	2.960
$\kappa_{(T=3K)}\left(\frac{10^{-5}\times W}{cm\times K}\right)$	↘	6.511	5.675	2.466	1.574
$\kappa_{(T=80K)}\left(\frac{10^{-4}\times W}{cm\times K}\right)$	↘	19.710	17.373	8.583	5.489
$-S_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$	↘	3.225	3.372	5.164	7.003
$-S_{(T=80K)}\left(\frac{10^{-5}\times V}{K}\right)$	↘	7.798	8.085	11.123	13.926
$-VC1_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$	↘	2.149	2.247	3.440	4.662
$-VC1_{(T=80K)}\left(\frac{10^{-5}\times V}{K}\right)$	↘	4.249	4.331	5.409	6.171
$-VC2_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$	↘	6.448	6.742	10.320	13.986
$-VC2_{(T=80K)}\left(\frac{10^{-3}\times V}{K}\right)$	↘	3.399	3.465	4.327	4.937
$-Ts_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$	↘	3.224	3.371	5.160	6.993
$-Ts_{(T=80K)}\left(\frac{10^{-5}\times V}{K}\right)$	↘	6.373	6.496	8.114	9.257
$-Pt_{(T=3K)}(10^{-5}\times V)$	↘	0.967	1.012	1.549	2.101
$-Pt_{(T=80K)}(10^{-3}\times V)$	↘	6.239	6.468	8.899	11.141
$ZT_{(T=3K)}(10^{-4})$	↗	4.258	4.655	10.915	20.074
$ZT_{(T=80K)}(10^{-1})$	↗	2.489	2.676	5.065	7.939

For **x=0.5** and **N=2.5×10^{18} cm^{-3}**, one has:

$\xi_{n(T=3K)}$	↘	159.415	155.272	125.305	111.952
$\xi_{n(T=80K)}$	↘	6.191	6.040	4.944	4.428
$\kappa_{(T=3K)}\left(\frac{10^{-5}\times W}{cm\times K}\right)$	↘	6.715	5.960	3.290	2.651
$\kappa_{(T=80K)}\left(\frac{10^{-4}\times W}{cm\times K}\right)$	↘	20.850	18.646	11.019	9.179
$-S_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$	↘	3.556	3.651	4.524	5.063
$-S_{(T=80K)}\left(\frac{10^{-5}\times V}{K}\right)$	↘	8.434	8.610	10.107	10.965
$-VC1_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$	↘	2.370	2.433	3.042	3.373
$-VC1_{(T=80K)}\left(\frac{10^{-5}\times V}{K}\right)$	↘	4.423	4.467	4.880	5.308
$-VC2_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$	↘	7.110	7.299	9.043	10.119
$-VC2_{(T=80K)}\left(\frac{10^{-3}\times V}{K}\right)$	↘	3.538	3.574	3.904	4.246
$-Ts_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$	↘	3.555	3.650	4.521	5.060
$-Ts_{(T=80K)}\left(\frac{10^{-5}\times V}{K}\right)$	↘	6.635	6.700	7.321	7.961
$-Pt_{(T=3K)}(10^{-5}\times V)$	↘	1.067	1.095	1.357	1.519
$-Pt_{(T=80K)}(10^{-3}\times V)$	↘	6.747	6.888	8.086	8.772
$ZT_{(T=3K)}(10^{-4})$	↗	5.177	5.457	8.377	10.494
$ZT_{(T=80K)}(10^{-1})$	↗	2.912	3.034	4.182	4.922

For **x=1** and **N=1×10^{18} cm^{-3}**, one has:

$\xi_{n(T=3K)}$	↘	139.819	137.918	124.568	118.886
$\xi_{n(T=80K)}$	↘	5.479	5.410	4.916	4.701
$\kappa_{(T=3K)}\left(\frac{10^{-5}\times W}{cm\times K}\right)$	↘	6.843	6.138	3.797	3.293
$\kappa_{(T=80K)}\left(\frac{10^{-4}\times W}{cm\times K}\right)$	↘	22.107	19.917	12.742	11.211
$-S_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$	↘	4.054	4.110	4.551	4.768

$-S_{(T=80K)}\left(\frac{10^{-5}\times V}{K}\right)$ ↘	9.326	9.422	10.151	10.499
$-VC1_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$ ↘	2.702	2.739	3.032	3.177
$-VC1_{(T=80K)}\left(\frac{10^{-5}\times V}{K}\right)$ ↘	4.642	4.667	4.897	5.049
$-VC2_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$ ↘	8.105	8.217	9.096	9.530
$-VC2_{(T=80K)}\left(\frac{10^{-3}\times V}{K}\right)$ ↘	3.714	3.733	3.918	4.039
$-Ts_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$ ↘	4.053	4.108	4.548	4.765
$-Ts_{(T=80K)}\left(\frac{10^{-5}\times V}{K}\right)$ ↘	6.963	7.000	7.345	7.573
$-Pt_{(T=3K)}(10^{-5}\times V)$ ↘	1.216	1.233	1.365	1.430
$-Pt_{(T=80K)}(10^{-3}\times V)$ ↘	7.461	7.537	8.121	8.399
$ZT_{(T=3K)}(10^{-4})$ ↗	6.729	6.916	8.477	9.306
$ZT_{(T=80K)}(10^{-1})$ ↗	3.560	3.634	4.218	4.512

In the $\mathbf{Y(x)\equiv CdS_{1-x}Se_x}$ **-crystalline alloy** and for T=3K and 80K, the numerical results of various thermoelectric coefficients are reported. Further, their variations with increasing $r_{d(a)}$ are represented by the arrows: ↗ (increase), and ↘ (decrease).

Donor	P	As	Sb	Sn
For **x=0** and **N=5×10^{18} cm^{-3}**, one has:				
$\xi_{n(T=3K)}$ ↘	175.787	168.118	109.771	80.924
$\xi_{n(T=80K)}$ ↘	6.786	6.507	4.339	2.960
$\kappa_{(T=3K)}\left(\frac{10^{-5}\times W}{cm\times K}\right)$ ↘	6.511	5.675	2.466	1.574
$\kappa_{(T=80K)}\left(\frac{10^{-4}\times W}{cm\times K}\right)$ ↘	19.710	17.373	8.583	5.489
$-S_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$ ↘	3.225	3.372	5.164	7.003
$-S_{(T=80K)}\left(\frac{10^{-5}\times V}{K}\right)$ ↘	7.798	8.085	11.123	13.926
$-VC1_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$ ↘	2.149	2.247	3.440	4.662
$-VC1_{(T=80K)}\left(\frac{10^{-5}\times V}{K}\right)$ ↘	4.249	4.331	5.409	6.171
$-VC2_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$ ↘	6.448	6.742	10.320	13.986
$-VC2_{(T=80K)}\left(\frac{10^{-3}\times V}{K}\right)$ ↘	3.399	3.465	4.327	4.937
$-Ts_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$ ↘	3.224	3.371	5.160	6.993
$-Ts_{(T=80K)}\left(\frac{10^{-5}\times V}{K}\right)$ ↘	6.373	6.496	8.114	9.257
$-Pt_{(T=3K)}(10^{-5}\times V)$ ↘	0.967	1.012	1.549	2.101
$-Pt_{(T=80K)}(10^{-3}\times V)$ ↘	6.239	6.468	8.899	11.141
$ZT_{(T=3K)}(10^{-4})$ ↗	4.258	4.655	10.915	20.074
$ZT_{(T=80K)}(10^{-1})$ ↗	2.489	2.676	5.065	7.939
For **x=0.5** and **N=2.5×10^{18} cm^{-3}**, one has:				
$\xi_{n(T=3K)}$ ↘	148.308	143.590	108.940	93.067
$\xi_{n(T=80K)}$ ↘	5.788	5.616	4.305	3.589
$\kappa_{(T=3K)}\left(\frac{10^{-5}\times W}{cm\times K}\right)$ ↘	6.066	5.354	2.763	2.112
$\kappa_{(T=80K)}\left(\frac{10^{-4}\times W}{cm\times K}\right)$ ↘	19.239	17.151	9.630	7.472
$-S_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$ ↘	3.822	3.948	5.203	6.090

$-S_{(T=80K)}\left(\frac{10^{-5}\times V}{K}\right)$	↘	8.920	9.142	11.185	12.583
$-VC1_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$	↘	2.547	2.631	3.466	4.056
$-VC1_{(T=80K)}\left(\frac{10^{-5}\times V}{K}\right)$	↘	4.542	4.596	5.450	6.353
$-VC2_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$	↘	7.642	7.893	10.398	12.167
$-VC2_{(T=80K)}\left(\frac{10^{-3}\times V}{K}\right)$	↘	3.634	3.676	4.360	5.082
$-Ts_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$	↘	3.821	3.946	5.199	6.084
$-Ts_{(T=80K)}\left(\frac{10^{-5}\times V}{K}\right)$	↘	6.814	6.894	8.176	9.529
$-Pt_{(T=3K)}(10^{-5}\times V)$	↘	1.147	1.184	1.561	1.827
$-Pt_{(T=80K)}(10^{-3}\times V)$	↘	7.136	7.313	8.948	10.067
$ZT_{(T=3K)}(10^{-4})$	↗	5.981	6.380	11.082	15.181
$ZT_{(T=80K)}(10^{-1})$	↗	3.257	3.421	5.121	6.482
For **x=1** and **N=1.3×10^{18} cm^{-3}**, one has:					
$\xi_{n(T=3K)}$	↘	141.723	139.291	122.076	114.662
$\xi_{n(T=80K)}$	↘	5.548	5.460	4.822	4.536
$\kappa_{(T=3K)}\left(\frac{10^{-5}\times W}{cm\times K}\right)$	↘	6.647	5.946	3.575	3.047
$\kappa_{(T=80K)}\left(\frac{10^{-4}\times W}{cm\times K}\right)$	↘	21.380	19.233	12.074	10.486
$-S_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$	↘	4.000	4.070	4.643	4.944
$-S_{(T=80K)}\left(\frac{10^{-5}\times V}{K}\right)$	↘	9.232	9.352	10.300	10.777
$-VC1_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$	↘	2.665	2.712	3.093	3.293
$-VC1_{(T=80K)}\left(\frac{10^{-5}\times V}{K}\right)$	↘	4.618	4.649	4.958	5.195
$-VC2_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$	↘	7.996	8.135	9.281	9.880
$-VC2_{(T=80K)}\left(\frac{10^{-3}\times V}{K}\right)$	↘	3.695	3.719	3.966	4.156
$-Ts_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$	↘	3.998	4.067	4.640	4.940
$-Ts_{(T=80K)}\left(\frac{10^{-5}\times V}{K}\right)$	↘	6.928	6.973	7.436	7.793
$-Pt_{(T=3K)}(10^{-5}\times V)$	↘	1.200	1.221	1.393	1.483
$-Pt_{(T=80K)}(10^{-3}\times V)$	↘	7.386	7.482	8.240	8.621
$ZT_{(T=3K)}(10^{-4})$	↗	6.549	6.780	8.826	10.004
$ZT_{(T=80K)}(10^{-1})$	↗	3.489	3.580	4.343	4.754

Table 4p:

In the **$X(x)\equiv CdS_{1-x}Te_x$ -crystalline alloy** and for T=3K and 80K, the numerical results of various thermoelectric coefficients are reported. Further, their variations with increasing $r_{d(a)}$ are represented by the arrows: ↗ (increase), and ↘ (decrease).

Acceptor		Ga	Mg	In	Cd
For x=0 and **N=8.5×10^{19} cm^{-3}**, one has:					
$\xi_{n(T=3K)}$	↘	172.057	101.469	90.903	87.152
$\xi_{n(T=80K)}$	↘	6.650	3.984	3.481	3.289
$\kappa_{(T=3K)}\left(\frac{10^{-5}\times W}{cm\times K}\right)$	↘	5.990	2.825	2.434	2.300
$\kappa_{(T=80K)}\left(\frac{10^{-3}\times W}{cm\times K}\right)$	↘	1.823	0.997	0.860	0.810

$-S_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$	↘	3.295	5.586	6.235	6.503
$-S_{(T=80K)}\left(\frac{10^{-5}\times V}{K}\right)$	↘	7.936	11.788	12.809	13.218
$-VC1_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$	↘	2.196	3.720	4.152	4.330
$-VC1_{(T=80K)}\left(\frac{10^{-5}\times V}{K}\right)$	↘	4.289	5.877	6.431	6.476
$-VC2_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$	↘	6.588	11.162	12.456	12.990
$-VC2_{(T=80K)}\left(\frac{10^{-3}\times V}{K}\right)$	↘	3.431	4.702	5.145	5.181
$-Ts_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$	↘	3.294	5.581	6.228	6.495
$-Ts_{(T=80K)}\left(\frac{10^{-5}\times V}{K}\right)$	↘	6.433	8.816	9.647	9.714
$-Pt_{(T=3K)}(10^{-5}\times V)$	↘	0.988	1.676	1.870	1.951
$-Pt_{(T=80K)}(10^{-3}\times V)$	↘	6.348	9.430	10.247	10.574
$ZT_{(T=3K)}(10^{-4})$	↗	4.444	12.773	15.912	17.310
$ZT_{(T=80K)}(10^{-1})$	↗	2.578	5.688	6.716	7.152

For x=0.5 and **N=8×10^{19} cm^{-3}** one has:

$\xi_{n(T=3K)}$	↘	183.717	129.410	121.787	119.129
$\xi_{n(T=80K)}$	↘	7.075	5.097	4.811	4.710
$\kappa_{(T=3K)}\left(\frac{10^{-5}\times W}{cm\times K}\right)$	↘	7.075	4.169	3.827	3.710
$\kappa_{(T=80K)}\left(\frac{10^{-3}\times W}{cm\times K}\right)$	↘	2.120	1.381	1.293	1.262
$-S_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$	↘	3.086	4.380	4.654	4.758
$-S_{(T=80K)}\left(\frac{10^{-5}\times V}{K}\right)$	↘	7.520	9.873	10.317	10.483
$-VC1_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$	↘	2.057	2.918	3.101	3.170
$-VC1_{(T=80K)}\left(\frac{10^{-5}\times V}{K}\right)$	↘	4.063	4.798	4.965	5.041
$-VC2_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$	↘	6.170	8.756	9.303	9.511
$-VC2_{(T=80K)}\left(\frac{10^{-3}\times V}{K}\right)$	↘	3.330	3.838	3.972	4.033
$-Ts_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$	↘	3.085	4.378	4.651	4.755
$-Ts_{(T=80K)}\left(\frac{10^{-5}\times V}{K}\right)$	↘	6.244	7.197	7.448	7.562
$-Pt_{(T=3K)}(10^{-5}\times V)$	↘	0.926	1.314	1.396	1.427
$-Pt_{(T=80K)}(10^{-3}\times V)$	↘	6.016	7.898	8.254	8.387
$ZT_{(T=3K)}(10^{-4})$	↗	3.898	7.854	8.868	9.268
$ZT_{(T=80K)}(10^{-1})$	↗	2.315	3.990	4.358	4.498

For x=1 and **N=7.5×10^{19} cm^{-3}** one has:

$\xi_{n(T=3K)}$	↘	187.995	143.936	137.922	135.838
$\xi_{n(T=80K)}$	↘	7.231	5.629	5.410	5.334
$\kappa_{(T=3K)}\left(\frac{10^{-5}\times W}{cm\times K}\right)$	↘	7.900	5.156	4.841	4.734
$\kappa_{(T=80K)}\left(\frac{10^{-3}\times W}{cm\times K}\right)$	↘	2.355	1.650	1.571	1.544
$-S_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$	↘	3.016	3.938	4.110	4.173
$-S_{(T=80K)}\left(\frac{10^{-5}\times V}{K}\right)$	↘	7.377	9.125	9.421	9.528
$-VC1_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$	↘	2.010	2.624	2.738	2.781
$-VC1_{(T=80K)}\left(\frac{10^{-5}\times V}{K}\right)$	↘	4.116	4.592	4.666	4.696

$-VC2_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$ ↘	6.030	7.873	8.216	8.342
$-VC2_{(T=80K)}\left(\frac{10^{-3}\times V}{K}\right)$ ↘	3.293	3.673	3.733	3.756
$-Ts_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$ ↘	3.015	3.936	4.108	4.171
$-Ts_{(T=80K)}\left(\frac{10^{-5}\times V}{K}\right)$ ↘	6.174	6.888	7.000	7.043
$-Pt_{(T=3K)}(10^{-5}\times V)$ ↘	0.905	1.181	1.233	1.252
$-Pt_{(T=80K)}(10^{-3}\times V)$ ↘	5.902	7.300	7.537	7.623
$ZT_{(T=3K)}(10^{-4})$ ↗	3.723	6.349	6.915	7.129
$ZT_{(T=80K)}(10^{-1})$ ↗	2.228	3.408	3.633	3.716

In the $\mathbf{Y(x) \equiv CdS_{1-x}Se_x - alloy}$ and for T=3K and 80K, the numerical results of various thermoelectric coefficients are reported. Further, their variations with increasing $r_{d(a)}$ are represented by the arrows: ↗ (increase), and ↘ (decrease).

Acceptor	Ga	Mg	In	Cd
For x=0 and **N=8.5×10^{19} cm^{-3}**, one has:				
$\xi_{n(T=3K)}$ ↘	172.057	101.469	90.903	87.152
$\xi_{n(T=80K)}$ ↘	6.650	3.984	3.481	3.289
$\kappa_{(T=3K)}\left(\frac{10^{-5}\times W}{cm\times K}\right)$ ↘	5.990	2.825	2.434	2.300
$\kappa_{(T=80K)}\left(\frac{10^{-3}\times W}{cm\times K}\right)$ ↘	1.823	0.997	0.860	0.810
$-S_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$ ↘	3.295	5.586	6.235	6.503
$-S_{(T=80K)}\left(\frac{10^{-5}\times V}{K}\right)$ ↘	7.936	11.788	12.809	13.218
$-VC1_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$ ↘	2.196	3.720	4.152	4.330
$-VC1_{(T=80K)}\left(\frac{10^{-5}\times V}{K}\right)$ ↘	4.289	5.877	6.431	6.476
$-VC2_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$ ↘	6.588	11.162	12.456	12.990
$-VC2_{(T=80K)}\left(\frac{10^{-3}\times V}{K}\right)$ ↘	3.431	4.702	5.145	5.181
$-Ts_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$ ↘	3.294	5.581	6.228	6.495
$-Ts_{(T=80K)}\left(\frac{10^{-5}\times V}{K}\right)$ ↘	6.433	8.816	9.647	9.714
$-Pt_{(T=3K)}(10^{-5}\times V)$ ↘	0.988	1.676	1.870	1.951
$-Pt_{(T=80K)}(10^{-3}\times V)$ ↘	6.348	9.430	10.247	10.574
$ZT_{(T=3K)}(10^{-4})$ ↗	4.444	12.773	15.912	17.310
$ZT_{(T=80K)}(10^{-1})$ ↗	2.578	5.688	6.716	7.152
For x=0.5 and **N=4×10^{19} cm^{-3}** one has:				
$\xi_{n(T=3K)}$ ↘	158.477	118.682	113.210	111.310
$\xi_{n(T=80K)}$ ↘	6.157	4.692	4.478	4.402
$\kappa_{(T=3K)}\left(\frac{10^{-5}\times W}{cm\times K}\right)$ ↘	6.162	3.915	3.655	3.567
$\kappa_{(T=80K)}\left(\frac{10^{-3}\times W}{cm\times K}\right)$ ↘	1.916	1.334	1.262	1.237
$-S_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$ ↘	3.577	4.776	5.007	5.092
$-S_{(T=80K)}\left(\frac{10^{-5}\times V}{K}\right)$ ↘	8.474	10.512	10.877	11.011
$-VC1_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$ ↘	2.384	3.182	3.336	3.392
$-VC1_{(T=80K)}\left(\frac{10^{-5}\times V}{K}\right)$ ↘	4.433	5.055	5.253	5.336

$-VC2_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$	↘	7.152	9.546	10.007	10.177
$-VC2_{(T=80K)}\left(\frac{10^{-3}\times V}{K}\right)$	↘	3.546	4.044	4.203	4.269
$-Ts_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$	↘	3.576	4.773	5.003	5.089
$-Ts_{(T=80K)}\left(\frac{10^{-5}\times V}{K}\right)$	↘	6.649	7.582	7.880	8.005
$-Pt_{(T=3K)}(10^{-5}\times V)$	↘	1.073	1.433	1.502	1.528
$-Pt_{(T=80K)}(10^{-3}\times V)$	↘	6.779	8.409	8.701	8.809
$ZT_{(T=3K)}(10^{-4})$	↗	5.238	9.338	10.260	10.615
$ZT_{(T=80K)}(10^{-1})$	↗	2.939	4.523	4.842	4.963
For x=1 and **N=1.5×10^{19} cm^{-3}** one has:					
$\xi_{n(T=3K)}$	↘	129.172	107.264	104.350	103.346
$\xi_{n(T=80K)}$	↘	5.088	4.235	4.111	4.067
$\kappa_{(T=3K)}\left(\frac{10^{-5}\times W}{cm\times K}\right)$	↘	5.533	3.981	3.808	3.750
$\kappa_{(T=80K)}\left(\frac{10^{-3}\times W}{cm\times K}\right)$	↘	1.834	1.392	1.338	1.320
$-S_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$	↘	4.388	5.284	5.432	5.485
$-S_{(T=80K)}\left(\frac{10^{-5}\times V}{K}\right)$	↘	9.887	11.313	11.545	11.628
$-VC1_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$	↘	2.924	3.520	3.618	3.653
$-VC1_{(T=80K)}\left(\frac{10^{-5}\times V}{K}\right)$	↘	4.803	5.538	5.703	5.763
$-VC2_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$	↘	8.772	10.560	10.855	10.960
$-VC2_{(T=80K)}\left(\frac{10^{-3}\times V}{K}\right)$	↘	3.843	4.430	4.562	4.610
$-Ts_{(T=3K)}\left(\frac{10^{-6}\times V}{K}\right)$	↘	4.386	5.280	5.427	5.480
$-Ts_{(T=80K)}\left(\frac{10^{-5}\times V}{K}\right)$	↘	7.204	8.307	8.554	8.644
$-Pt_{(T=3K)}(10^{-5}\times V)$	↘	1.316	1.585	1.629	1.645
$-Pt_{(T=80K)}(10^{-3}\times V)$	↘	7.909	9.050	9.236	9.303
$ZT_{(T=3K)}(10^{-4})$	↗	7.884	11.431	12.078	12.313
$ZT_{(T=80K)}(10^{-1})$	↗	4.001	5.239	5.456	5.535

Table 5n

In the **$X(x)\equiv CdS_{1-x}Te_x$-crystalline alloy**, for a given N and with increasing T, the reduced Fermi-energy ξ_n decreases, and other thermoelectric coefficients are in variations, as indicated by the arrows as: (increase: ↗, decrease: ↘). One notes here that with increasing T: (i) for $\xi_n\simeq1.8138$, while the numerical results of S present a same minimum $(S)_{min.}\left(\simeq-1.563\times10^{-4}\frac{V}{K}\right)$, those of ZT show a same maximum $(ZT)_{max.}=1$, (ii) for $\xi_n=1$, those of S, ZT, $(ZT)_{Mott}$, VC1, and T_s present the same results: $-1.322\times10^{-4}\frac{V}{K}$, 0.715, 3.290, $1.105\times10^{-4}\frac{V}{K}$, and $1.657\times10^{-4}\frac{V}{K}$, respectively, and (iii) for $\xi_n\simeq1.8138$, $(ZT)_{Mott}=1$.

For x=0,

In the degenerate P- $X(x)-$ alloy, for $N=2\times N_{CDn}(r_p)=2.3039912\times10^{18}$ cm^{-3}, one gets:

(K)	↗	104.111		**106.37815**		108.666		**144.755**	144.903
ξ_n	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322** ↗	− 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715** ↘	0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105** ↗	1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$		−6.381	↗	**0**	↗	6.834	↗	159.945 ↗	160.702

$T_s\left(10^{-4}\frac{V}{K}\right)$	−0.092	↗	0	↗	0.094	↗	**1.657**	↗	1.663
Pt $(10^{-3}V)$	−16.2621	↘	−16.6269	↘	−16.9736	↘	−19.1324	↗	−19.1273

In the degenerate As- $X(x)-$ alloy, for $N = 2 \times N_{CDn}\,(r_{As}) = 2.8021636 \times 10^{18}\ cm^{-3}$, one gets:

T(K)	↗	118.622		**121.20698**		123.814		**164.933**	144.903
ξ_n	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322**	↗ − 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$		−7.276	↗	**0**	↗	**7.788**	↗	182.238	↗ 183.108
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
Pt $(10^{-3}V)$		−18.5287	↘	−18.9446	↘	−19.3397	↘	−21.7994	↗ −21.7936

In the degenerate Sb- $X(x)-$ alloy, for $N = 2 \times N_{CDn}\,(r_{Sb}) = 6.2027052 \times 10^{18}\ cm^{-3}$, one gets:

T(K)	↗	201.476		**205.86668**		210.296		**280.1353**	280.423
ξ_n	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322**	↗ − 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$		--12.358	↗	**0**	↗	**13.231**	↗	309.533	↗ 311.004
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
Pt $(10^{-3}V)$		−31.4705	↘	−32.1769	↘	−32.8482	↘	−37.0256	↗ −37.0158

In the degenerate Sn- $X(x)-$ alloy, for $N = 2 \times N_{CDn}\,(r_{Sn}) = 7.5967124 \times 10^{18}\ cm^{-3}$, one gets:

T(K)	↗	230.632		**235.65813**		240.728		**320.6747**	321.003
ξ_n	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322**	↗ − 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$ −		14.146	↗	**0**	↗	**15.145**	↗	354.328	↗ 356.007
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
Pt $(10^{-3}V)$		−36.0247	↘	−36.8333	↘	−37.6017	↘	−42.3837	↗ −42.3725

For x=0.5,

In the degenerate P- $X(x)-$ alloy, for $N = 2 \times N_{CDn}\,(r_p) = 7.5964624 \times 10^{17}\ cm^{-3}$, one gets:

T(K)	↗	67.044		**68.50458**		69.978		**93.218446**	93.314
ξ_n	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322**	↗ − 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$		−4.111	↗	**0**	↗	**4.401**	↗	103.001	↗ 103.490
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663

$Pt\,(10^{-3}V)$		−10.4729	↘	−10.7072	↘	−10.9306	↘	−12.3207	↗ −12.3175

In the degenerate As- $X(x)-$ alloy, for $N = 2 \times N_{CDn}\,(r_{As}) = 9.2389806 \times 10^{17}\ cm^{-3}$, one gets:

T(K)	↗	76.3891		**78.05392**		79.733		**106.21283**	93.314
ξ_n	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322**	↗ − 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$		−4.686	↗	**0**	↗	**5.016**	↗	117.359	↗ 117.912
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\,(10^{-3}V)$		−11.9320	↘	−12.1998	↘	−12.4543	↘	−14.0381	↗ −14.0345

In the degenerate Sb- $X(x)-$ alloy, for $N = 2 \times N_{CDn}\,(r_{Sb}) = 2.0450866 \times 10^{18}\ cm^{-3}$, one gets:

T(K)	↗	129.7448		**132.57241**		135.424		**180.39953**	180.584
ξ_n	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322**	↗ − 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$		−7.958	↗	**0**	↗	**8.518**	↗	199.331	↗ 200.275
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\,(10^{-3}V)$		−20.2661	↘	−20.7210	↘	−21.1532	↘	−23.8434	↗ −23.8372

In the degenerate Sn- $X(x)-$ alloy, for $N = 2 \times N_{CDn}\,(r_{Sn}) = 2.5047032 \times 10^{18}\ cm^{-3}$, one gets:

T(K)	↗	148.5205		**151.757275**		155.0225		**206.50558**	206.7174
ξ_n	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322**	↗ − 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$		−9.110	↗	**0**	↗	**9.754**	↗	228.177	↗ 229.261
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\,(10^{-3}V)$		−23.1989	↘	−23.7196	↘	−24.2145	↘	−27.2939	↗ −27.2867

For x=1,

In the degenerate P- $X(x)-$ alloy, for $N = 2 \times N_{CDn}\,(r_p) = 1.7187174 \times 10^{17}\ cm^{-3}$, one gets:

T(K)	↗	38.2573		**39.091072**		39.932		**53.193656**	53.248
ξ_n	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322**	↗ − 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$		−2.347	↗	**0**	↗	**2.512**	↗	58.776	↗ 59.054
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\,(10^{-3}V)$		−5.9758	↘	−6.1099	↘	−6.2374	↘	−7.0306	↗ −7.0288

In the degenerate As- $X(x)-$ alloy, for $N=2\times N_{CDn}(r_{As})=2.090341\times 10^{17}\ cm^{-3}$, one gets:

T(K)	↗	43.5903		**44.540254**		45.4985		**60.60869**	60.6708
ξ_n	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322**	↗ − 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$		−2.674	↗	**0**	↗	2.862	↗	66.969	↗ 67.286
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\ (10^{-3}V)$		−6.8088	↘	−6.9616	↘	−7.1069	↘	−8.0107	↗ −8.0085

In the degenerate Sb- $X(x)-$ alloy, for $N=2\times N_{CDn}(r_{Sb})=4.6270566\times 10^{17}\ cm^{-3}$, one gets:

T(K)	↗	74.037		**75.650383**		77.2781		**102.94219**	103.047
ξ_n	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322**	↗ − 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$		−4.541	↗	**0**	↗	4.862	↗	113.745	↗ 114.281
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\ (10^{-3}V)$		−11.5646	↘	−11.8241	↘	−12.0708	↘	−13.6059	↗ −13.6023

In the degenerate Sn- $X(x)-$ alloy, for $N=2\times N_{CDn}(r_{Sn})=5.6669496\times 10^{17}\ cm^{-3}$, one gets:

T(K)	↗	84.751		**86.597926**		88.4611		**117.83919**	117.96
ξ_n	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322**	↗ − 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$		−5.198	↗	**0**	↗	5.566	↗	130.206	↗ 130.824
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\ (10^{-3}V)$		−13.2381	↘	−13.5352	↘	−13.8176	↘	−15.5748	↗ −15.5707

In the $Y(x)\equiv CdS_{1-x}Se_x-$ **alloy**, for a given N and with increasing T, the reduced Fermi-energy ξ_n decreases, and other thermoelectric coefficients are in variations, as indicated by the arrows as: (increase: ↗, decrease: ↘). One notes here that with increasing T: (i) for $\xi_n\simeq 1.8138$, while the numerical results of S present a same minimum $(S)_{min.}\left(\simeq -1.563\times 10^{-4}\frac{V}{K}\right)$, those of ZT show a same maximum $(ZT)_{max.}=1$, (ii) for $\xi_n=1$, those of S, ZT, $(ZT)_{Mott}$, VC1, and T_s present the same results: $-1.322\times 10^{-4}\frac{V}{K}$, 0.715, 3.290, $1.105\times 10^{-4}\frac{V}{K}$, and $1.657\times 10^{-4}\frac{V}{K}$, respectively, and (iii) for $\xi_n\simeq 1.8138$, $(ZT)_{Mott}=1$.

For x=0,

In the degenerate P- $Y(x)-$ alloy, for $N=2\times N_{CDn}(r_p)=2.3039912\times 10^{18}\ cm^{-3}$, one gets:

T(K)	↗	104.111		**106.37815**		108.666		**144.755**	144.903
ξ_n	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322**	↗ − 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mott}$	↗	0.931		**1**		1.074		**3.290**	3.306

$VC1\left(10^{-4}\frac{V}{K}\right)$	−0.061	↗	0	↗	0.063	↗	**1.105**	↗	1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$	−6.381	↗	0	↗	6.834	↗	159.945	↗	160.702
$T_s\left(10^{-4}\frac{V}{K}\right)$	−0.092	↗	0	↗	0.094	↗	**1.657**	↗	1.663
$Pt\ (10^{-3}V)$	−16.2621	↘	−16.6269	↘	−16.9736	↘	−19.1324	↗	−19.1273

In the degenerate As- $Y(x)-$ alloy, for $N = 2 \times N_{CDn}\,(r_{As}) = 2.8021636 \times 10^{18}\ cm^{-3}$, one gets:

T(K)	↗	118.622		**121.20698**		123.814		**164.933**	144.903
ξ_n	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322**	↗ − 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	0	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$		−7.276	↗	0	↗	7.788	↗	182.238	↗ 183.108
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	0	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\ (10^{-3}V)$		−18.5287	↘	−18.9446	↘	−19.3397	↘	−21.7994	↗ −21.7936

In the degenerate Sb- $Y(x)-$ alloy, for $N = 2 \times N_{CDn}\,(r_{Sb}) = 6.2027052 \times 10^{18}\ cm^{-3}$, one gets:

T(K)	↗	201.476		**205.86668**		210.296		**280.1353**	280.423
ξ_n	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322**	↗ − 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	0	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-4}\frac{V}{K}\right)-$		12.358	↗	0	↗	13.231	↗	309.533	↗ 311.004
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	0	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\ (10^{-3}V)$		−31.4705	↘	−32.1769	↘	−32.8482	↘	−37.0256	↗ −37.0158

In the degenerate Sn- $Y(x)-$ alloy, for $N = 2 \times N_{CDn}\,(r_{Sn}) = 7.5967124 \times 10^{18}\ cm^{-3}$, one gets:

T(K)	↗	230.632		**235.65813**		240.728		**320.6747**	321.003
ξ_n	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322**	↗ − 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	0	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-4}\frac{V}{K}\right)-$		14.146	↗	0	↗	15.145	↗	354.328	↗ 356.007
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	0	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\ (10^{-3}V)$		−36.0247	↘	−36.8333	↘	−37.6017	↘	−42.3837	↗ −42.3725

For x=0.5,

In the degenerate P- $Y(x)-$ alloy, for $N = 2 \times N_{CDn}\,(r_p) = 8.9809256 \times 10^{17}\ cm^{-3}$, one gets:

T(K)	↗	71.2975		**72.851285**		74.4187		**99.13328**	99.23499
ξ_n	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322**	↗ − 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	0	↗	0.063	↗	**1.105**	↗ 1.109

$VC2\left(10^{-4}\frac{V}{K}\right)$	−4.373	↗	**0**	↗	4.682	↗	109.537	↗	110.057
$T_s\left(10^{-4}\frac{V}{K}\right)$	−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗	1.663
$Pt\ (10^{-3}V)$	−11.1367	↘	−11.3866	↘	−11.6242	↘	−13.1024	↗	−13.0990

In the degenerate As- $Y(x)-$ alloy, for $N = 2 \times N_{CDn}\,(r_{As}) = 1.0922795 \times 10^{18}\ cm^{-3}$, one gets:

T(K)	↗	81.23617		**83.006543**		84.7925		**112.952173**	113.06807
ξ_n	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322**	↗ − 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$		−4.983	↗	**0**	↗	5.335	↗	124.806	↗ 125.399
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\ (10^{-3}V)$		−11.1367	↘	−12.9739	↘	−13.2446	↘	−14.9289	↗ −14.9250

In the degenerate Sb- $Y(x)-$ alloy, for $N = 2 \times N_{CDn}\,(r_{Sb}) = 2.4178058 \times 10^{18}\ cm^{-3}$, one gets:

T(K)	↗	137.9773		**140.984303**		144.0177		**191.84612**	192.0429
ξ_n	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322**	↗ − 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$		−8.463	↗	**0**	↗	9.061	↗	211.979	↗ 212.986
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\ (10^{-3}V)$		−21.5520	↘	−22.0358	↘	−22.4956	↘	−25.3563	↗ −25.3497

In the degenerate Sn- $Y(x)-$ alloy, for $N = 2 \times N_{CDn}\,(r_{Sn}) = 2.961188 \times 10^{18}\ cm^{-3}$, one gets:

T(K)	↗	157.9443		**161.386476**		164.8588		**219.60863**	219.8338
ξ_n	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322**	↗ − 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$		−9.688	↗	**0**	↗	**10.373**	↗	242.655	↗ 243.807
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\ (10^{-3}V)$		−24.6709	↘	−25.2247	↘	−25.7509	↘	−29.0257	↗ −29.0181

For x=1,

In the degenerate P- $Y(x)-$ alloy, for $N = 2 \times N_{CDn}\,(r_p) = 2.7554162 \times 10^{17}\ cm^{-3}$, one gets:

T(K)	↗	45.25856		**46.24488**		47.2398		**62.928287**	62.99285
ξ_n	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322**	↗ − 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$		−2.776	↗	**0**	↗	2.972	↗	69.532	↗ 69.862

$T_s\left(10^{-4}\frac{V}{K}\right)$	−0.092	↗	0	↗	0.094	↗	**1.657**	↗	1.663
Pt $(10^{-3}V)$	−7.0694	↘	−7.2281	↘	−7.3788	↘	−8.3172	↗	−8.3150

In the degenerate As- $Y(x)-$ alloy, for $N = 2 \times N_{CDn}\,(r_{As}) = 3.3511962 \times 10^{17}\ cm^{-3}$, one gets:

T(K)	↗	51.56745		**52.69128**		53.825		**71.700306**	71.77387
ξ_n	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322**	↗ − 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mott}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$		−3.163	↗	**0**	↗	3.387	↗	79.225	↗ 79.601
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
Pt $(10^{-3}V)$		−8.0548	↘	−8.2356	↘	−8.4075	↘	−9.4766	↗ −9.4741

In the degenerate Sb- $Y(x)-$ alloy, for $N = 2 \times N_{CDn}\,(r_{Sb}) = 7.418012 \times 10^{17}\ cm^{-3}$, one gets:

T(K)	↗	87.58592		**89.494675**		91.42018		**121.78098**	121.90592
ξ_n	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322**	↗ − 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mott}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$		−5.372	↗	**0**	↗	5.752	↗	134.561	↗ 135.200
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
Pt $(10^{-3}V)$		−13.6809	↘	−13.9880	↘	−14.2798	↘	−16.0958	↗ −16.0916

In the degenerate Sn- $Y(x)-$ alloy, for $N = 2 \times N_{CDn}\,(r_{Sn}) = 9.0851494 \times 10^{17}\ cm^{-3}$, one gets:

T(K)	↗	100.2606		**102.44566**		104.6499		**139.40419**	139.5472
ξ_n	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322**	↗ − 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mott}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$		−6.150	↗	**0**	↗	6.584	↗	154.034	↗ 154.765
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
Pt $(10^{-3}V)$		−15.661	↘	−16.0122	↘	−16.3463	↘	−18.4251	↗ −18.4202

Table 5p

In the $X(x) \equiv CdS_{1-x}Te_x$**-crystalline alloy**, for a given N and with increasing T, the reduced Fermi-energy ξ_p decreases, and other thermoelectric coefficients are in variations, as indicated by the arrows as: (increase: ↗, decrease: ↘). One notes here that with increasing T: (i) for $\xi_p \simeq 1.8138$, while the numerical results of S present a same minimum $(S)_{min.}\left(\simeq -1.563 \times 10^{-4}\frac{V}{K}\right)$, those of ZT show a same maximum $(ZT)_{max.} = 1$, (ii) for $\xi_p = 1$, those of S, ZT, $(ZT)_{Mott}$, VC1, and T_s present the same results: $-1.322 \times 10^{-4}\frac{V}{K}$, 0.715, 3.290, $1.105 \times 10^{-4}\frac{V}{K}$, and $1.657 \times 10^{-4}\frac{V}{K}$, respectively, and (iii) for $\xi_p \simeq 1.8138$, $(ZT)_{Mott} = 1$.

For x=0,

In the degenerate Ga- $X(x)-$ alloy, for $N = 2 \times N_{CD_p}(r_{Ga}) = 1.0889983 \times 10^{20}\ cm^{-3}$, one gets:

T(K)	↗	334.724		**342.0192**		349.378		**465.40683**	465.884
ξ_p	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗ −1.320
ZT		0.999	↗	**1**	↘	0.998	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-2}\frac{V}{K}\right)$		−0.205	↗	**0**	↗	0.219	↗	5.142	↗ 5.167
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\ (10^{-2}V)$		−5.2284	↘	−5.3457	↘	−5.4573	↘	−6.1513	↗ −6.1497

In the degenerate Mg- $X(x)-$ alloy, for $N = 2 \times N_{CD_p}(r_{Mg}) = 1.4233181 \times 10^{20}\ cm^{-3}$, one gets

T(K)	↗	400.132		**408.85281**		417.65		**556.35147**	556.92
ξ_p	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗ −1.320
ZT		0.999	↗	**1**	↘	0.998	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-2}\frac{V}{K}\right)$		−0.245	↗	**0**	↗	0.263	↗	6.147	↗ 6.167
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\ (10^{-2}V)$		−6.2501	↘	−6.3904	↘	−6.5237	↘	−7.3533	↗ −7.3514

In the degenerate In- $X(x)-$ alloy, for $N = 2 \times N_{CD_p}(r_{In}) = 1.4654004 \times 10^{20}\ cm^{-3}$, one gets:

T(K)	↗	407.9813		**416.87247**		425.84		**567.26432**	567.846
ξ_p	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗ −1.320
ZT		0.999	↗	**1**	↘	0.998	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-2}\frac{V}{K}\right)$		−0.250	↗	**0**	↗	0.268	↗	6.268	↗ 6.297
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\ (10^{-2}V)$		−6.3727	↘	−6.5157	↘	−6.6516	↘	−7.4975	↗ −7.4956

In the degenerate Cd- $X(x)-$ alloy, for $N = 2 \times N_{CD_p}(r_{Cd}) = 1.479774 \times 10^{20}\ cm^{-3}$, one gets:

T(K)	↗	410.644		**419.59401**		428.622		**570.9677**	571.553
ξ_p	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗ −1.320
ZT		0.999	↗	**1**	↘	0.998	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-2}\frac{V}{K}\right)$		−0.252	↗	**0**	↗	0.270	↗	6.309	↗ 6.338
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\ (10^{-2}V)$		−6.4142	↘	−6.5582	↘	−6.6951	↘	−7.5465	↗ −7.5445

For x=0.5,

In the degenerate Ga- $X(x)-$ alloy, for $N=2\times N_{CD_p}(r_{Ga})=9.1381736\ \times 10^{19}\ cm^{-3}$, one gets:

T(K)	↗	294.299		**300.71248**		307.183		**409.1982**	409.618
ξ_p	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗ −1.320
ZT		0.999	↗	**1**	↘	0.998	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-2}\frac{V}{K}\right)$		−0.180	↗	**0**	↗	0.193	↗	4.521	↗ 4.543
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\ (10^{-2}V)$		−4.5969	↘	−4.7001	↘	−4.7982	↘	−5.4084	↗ −5.4069

In the degenerate Mg- $X(x)-$ alloy, for $N=2\times N_{CD_p}(r_{Mg})=1.194357\times 10^{20}\ cm^{-3}$, one gets

T(K)	↗	351.807		**359.47439**		367.209		**489.1592**	489.661
ξ_p	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗ −1.320
ZT		0.999	↗	**1**	↘	0.998	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-2}\frac{V}{K}\right)$		−0.216	↗	**0**	↗	0.231	↗	5.405	↗ 5.430
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\ (10^{-2}V)$		−5.4952	↘	−5.6186	↘	−5.7358	↘	−6.4652	↗ −6.4635

In the degenerate In- $X(x)-$ alloy, for $N=2\times N_{CD_p}(r_{In})=1.2296698\times 10^{20}\ cm^{-3}$, one gets:

T(K)	↗	358.71		**366.52549**		374.412		**498.75405**	499.266
ξ_p	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗ −1.320
ZT		0.999	↗	**1**	↘	0.998	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-2}\frac{V}{K}\right)$		−0.220	↗	**0**	↗	0.235	↗	5.511	↗ 5.537
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\ (10^{-2}V)$		−5.6030	↘	−5.7288	↘	−5.8483	↘	−6.5920	↗ −6.5903

In the degenerate Cd- $X(x)-$ alloy, for $N=2\times N_{CD_p}(r_{Cd})=1.2417312\times 10^{20}\ cm^{-3}$, one gets:

T(K)	↗	361.05		**368.91834**		376.856		**502.01015**	502.525
ξ_p	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗ −1.320
ZT		0.999	↗	**1**	↘	0.998	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-2}\frac{V}{K}\right)$		−0.221	↗	**0**	↗	0.237	↗	5.547	↗ 5.573
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\ (10^{-2}V)$		−5.6396	↘	−5.7662	↘	−5.8865	↘	−6.6351	↗ −6.6333

For x=1,

In the degenerate Ga- $X(x)-$ alloy, for $N = 2 \times N_{CD_D}(r_{Ga}) = 7.7718202 \times 10^{19}\ cm^{-3}$, one gets:

T(K)	↗	261.118		**266.80841**		272.549		**363.06282**	363.435
ξ_p	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗ −1.320
ZT		0.999	↗	**1**	↘	0.998	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	0	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-2}\frac{V}{K}\right)$		−0.160	↗	0	↗	0.171	↗	4.012	↗ 4.031
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	0	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\,(10^{-2}V)$		−4.0787	↘	−4.1702	↘	−4.2572	↘	−4.7986	↗ −4.7973

In the degenerate Mg- $X(x)-$ alloy, for $N = 2 \times N_{CD_D}(r_{Mg}) = 1.015775 \times 10^{20}\ cm^{-3}$, one gets:

T(K)	↗	312.1425		**318.94516**		325.808		**434.00854**	434.4538
ξ_p	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗ −1.320
ZT		0.999	↗	**1**	↘	0.998	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	0	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-2}\frac{V}{K}\right)$		−0.191	↗	0	↗	0.205	↗	4.795	↗ 4.818
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	0	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\,(10^{-2}V)$		−4.8757	↘	−4.9851	↘	−5.0891	↘	−5.7363	↗ −5.7348

In the degenerate In- $X(x)-$ alloy, for $N = 2 \times N_{CD_D}(r_{In}) = 1.0458077 \times 10^{20}\ cm^{-3}$, one gets:

T(K)	↗	318.265		**325.20128**		332.198		**442.52163**	442.975
ξ_p	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗ −1.320
ZT		0.999	↗	**1**	↘	0.998	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	0	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-2}\frac{V}{K}\right)$		−0.195	↗	0	↗	0.209	↗	4.890	↗ 4.912
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	0	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\,(10^{-2}V)$		−4.9713	↘	−5.0829	↘	−5.1889	↘	−5.8488	↗ −5.8473

In the degenerate Cd- $X(x)-$ alloy, for $N = 2 \times N_{CD_D}(r_{In}) = 1.0560657 \times 10^{20}\ cm^{-3}$, one gets:

T(K)	↗	320.343		**327.32434**		334.367		**445.41062**	445.867
ξ_p	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗ −1.320
ZT		0.999	↗	**1**	↘	0.998	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	0	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-2}\frac{V}{K}\right)$		−0.196	↗	0	↗	0.210	↗	4.921	↗ 4.945
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	0	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\,(10^{-2}V)$		−5.0037	↘	−5.1161	↘	−5.2228	↘	−5.8870	↗ −8854

In the $\mathbf{Y(x) \equiv CdS_{1-x}Se_x - alloy}$, for a given N and with increasing T, the reduced Fermi-energy ξ_p decreases, and other thermoelectric coefficients are in variations, as indicated by the arrows as: (increase: ↗, decrease: ↘). One notes here that with increasing T: (i) for $\xi_p \simeq 1.8138$, while the numerical results of S present a same minimum $(S)_{min.}\left(\simeq -1.563\times 10^{-4}\frac{V}{K}\right)$, those of ZT show a same maximum $(ZT)_{max.}=1$, (ii) for $\xi_p = 1$, those of S, ZT, $(ZT)_{Mott}$, VC1, and T_s present the same results: $-1.322\times 10^{-4}\frac{V}{K}$, 0.715, 3.290, $1.105\times 10^{-4}\frac{V}{K}$, and $1.657\times 10^{-4}\frac{V}{K}$, respectively, and (iii) for $\xi_p \simeq 1.8138$, $(ZT)_{Mott}=1$.

For x=0,

In the degenerate Ga- $Y(x)-$ alloy, for $N = 2\times N_{CD_P}(r_{Ga}) = 1.0889983\times 10^{20}\ cm^{-3}$, one gets:

T(K)	↗	334.724		**342.0192**		349.378		**465.40683**	465.884
ξ_p	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗ −1.320
ZT		0.999	↗	**1**	↘	0.998	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-2}\frac{V}{K}\right)$		−0.205	↗	**0**	↗	0.219	↗	5.142	↗ 5.167
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\ (10^{-2}V)$		−5.2284	↘	−5.3457	↘	−5.4573	↘	−6.1513	↗ −6.1497

In the degenerate Mg- $Y(x)-$ alloy, for $N = 2\times N_{CD_P}(r_{Mg}) = 1.4233181\times 10^{20}\ cm^{-3}$, one gets

T(K)	↗	400.132		**408.85281**		417.65		**556.35147**	556.92
ξ_p	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗ −1.320
ZT		0.999	↗	**1**	↘	0.998	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-2}\frac{V}{K}\right)$		−0.245	↗	**0**	↗	0.263	↗	6.147	↗ 6.167
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\ (10^{-2}V)$		−6.2501	↘	−6.3904	↘	−6.5237	↘	−7.3533	↗ −7.3514

In the degenerate In- $Y(x)-$ alloy, for $N = 2\times N_{CD_P}(r_{In}) = 1.4654004\times 10^{20}\ cm^{-3}$, one gets:

T(K)	↗	407.9813		**416.87247**		425.84		**567.26432**	567.846
ξ_p	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗ −1.320
ZT		0.999	↗	**1**	↘	0.998	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-2}\frac{V}{K}\right)$		−0.250	↗	**0**	↗	0.268	↗	6.268	↗ 6.297
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\ (10^{-2}V)$		−6.3727	↘	−6.5157	↘	−6.6516	↘	−7.4975	↗ −7.4956

In the degenerate Cd- $Y(x)-$ alloy, for $N = 2\times N_{CD_P}(r_{Cd}) = 1.479774\times 10^{20}\ cm^{-3}$, one gets:

T(K)	↗	410.644		**419.59401**		428.622		**570.9677**	571.553
ξ_p	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗ −1.320
ZT		0.999	↗	**1**	↘	0.998	↘	**0.715**	↘ 0.713

$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	0	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-2}\frac{V}{K}\right)$		−0.252	↗	0	↗	0.270	↗	6.309	↗ 6.338
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	0	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\,(10^{-2}V)$		−6.4142	↘	−6.5582	↘	−6.6951	↘	−7.5465	↗ −7.5445

For x=0.5,

In the degenerate Ga- $Y(x)-$ alloy, for $N = 2\times N_{CD_p}(r_{Ga}) = 4.2729264\times 10^{19}\ cm^{-3}$, one gets:

T(K)	↗	229.734		**234.74039**		239.791		**319.42587**	319.753
ξ_p	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗ −1.320
ZT		0.999	↗	**1**	↘	0.998	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	0	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-2}\frac{V}{K}\right)$		−0.141	↗	0	↗	0.151	↗	3.529	↗ 3.546
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	0	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\,(10^{-2}V)$		−3.5884	↘	−3.6690	↘	−3.7455	↘	−4.2219	↗ −4.2207

In the degenerate Mg- $Y(x)-$ alloy, for $N = 2\times N_{CD_p}(r_{Mg}) = 5.5847044\times 10^{19}\ cm^{-3}$, one gets:

T(K)	↗	274.626		**280.61078**		286.648		**381.84455**	382.236
ξ_p	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗ −1.320
ZT		0.999	↗	**1**	↘	0.998	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	0	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-2}\frac{V}{K}\right)$		−0.168	↗	0	↗	0.180	↗	4.219	↗ 4.239
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	0	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\,(10^{-2}V)$		−4.2896	↘	−4.3859	↘	−4.4774	↘	−5.0468	↗ −5.0455

In the degenerate In- $Y(x)-$ alloy, for $N = 2\times N_{CD_p}(r_{In}) = 5.7498236\times 10^{19}\ cm^{-3}$, one gets:

T(K)	↗	280.0126		**286.11496**		292.271		**389.33444**	389.733
ξ_p	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗ −1.320
ZT		0.999	↗	**1**	↘	0.998	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	0	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-2}\frac{V}{K}\right)$		−0.172	↗	0	↗	0.184	↗	4.302	↗ 4.322
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	0	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\,(10^{-2}V)$		−4.3738	↘	−4.4720	↘	−4.5653	↘	−5.1458	↗ −5.1445

In the degenerate Cd- $Y(x)-$ alloy, for $N = 2\times N_{CD_p}(r_{Cd}) = 5.8062216\times 10^{19}\ cm^{-3}$, one gets.

T(K)	↗	281.8405		**287.98285**		294.179		**391.8762**	392.278
ξ_p	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗ −1.320
ZT		0.999	↗	**1**	↘	0.998	↘	**0.715**	↘ 0.713

$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	0	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-2}\frac{V}{K}\right)$		−0.173	↗	0	↗	0.185	↗	4.330	↗ 4.350
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	0	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\,(10^{-2}V)$		−4.4023	↘	−4.5012	↘	−4.5951	↘	−5.1794	↗ −5.1781

For x=1,

In the degenerate Ga- $Y(x)-$ alloy, for $N = 2\times N_{CDp}\,(r_{Ga}) = 1.3264601\times 10^{19}\ cm^{-3}$, one gets:

T(K)	↗	146.4037		**149.59434**		152.813		**203.56233**	203.7712
ξ_p	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗ −1.320
ZT		0.999	↗	**1**	↘	0.998	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	0	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-2}\frac{V}{K}\right)$		−0.090	↗	0	↗	0.096	↗	2.249	↗ 2.260
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	0	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\,(10^{-2}V)$		−2.2868	↘	−2.3381	↘	−2.3869	↘	−2.6905	↗ −2.6898

In the degenerate Mg- $Y(x)-$ alloy, for $N = 2\times N_{CDp}\,(r_{Mg}) = 1.7336801\times 10^{19}\ cm^{-3}$, one gets:

T(K)	↗	175.0123		**178.82641**		182.674		**243.34024**	243.589
ξ_p	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗ −1.320
ZT		0.999	↗	**1**	↘	0.998	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	0	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-2}\frac{V}{K}\right)$		−0.107	↗	0	↗	0.115	↗	2.689	↗ 2.701
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	0	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\,(10^{-2}V)$		−2.7337	↘	−2.7950	↘	−2.8534	↘	−3.2162	↗ −3.2154

In the degenerate In- $Y(x)-$ alloy, for $N = 2\times N_{CDp}\,(r_{In}) = 1.7849387\times 10^{19}\ cm^{-3}$, one gets:

T(K)	↗	178.445		**182.3341**		186.257		**248.11336**	248.367
ξ_p	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗ −1.320
ZT		0.999	↗	**1**	↘	0.998	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	0	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-2}\frac{V}{K}\right)$		−0.109	↗	0	↗	0.117	↗	2.741	↗ 2.754
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	0	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\,(10^{-2}V)$		−2.7873	↘	−2.8500	↘	−2.9093	↘	−3.2793	↗ −3.2784

In the degenerate Cd- $Y(x)-$ alloy, for $N = 2\times N_{CDp}\,(r_{In}) = 1.8024466\times 10^{19}\ cm^{-3}$, one gets:

T(K)	↗	179.610		**183.52446**		187.473		**249.73316**	249.989
ξ_p	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗ −1.320
ZT		0.999	↗	**1**	↘	0.998	↘	**0.715**	↘ 0.713

$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-2}\frac{V}{K}\right)$		−0.110	↗	**0**	↗	0.118	↗	2.759	↗ 2.772
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\,(10^{-2}V)$		−2.8055	↘	−2.8685	↘	−2.9283	↘	−3.3007	↗ −3.2999

Table 6n:

In the $\mathbf{X(x) \equiv CdS_{1-x}Te_x}$ **−crystalline alloy**, for a given T and with decreasing N, the reduced Fermi-energy ξ_n decreases, and other thermoelectric coefficients are in variations, as indicated by the arrows as: (increase: ↗, decrease: ↘). One notes here that with increasing T: (i) for $\xi_n \simeq 1.8138$, while the numerical results of S present a same minimum $(S)_{min.}\left(\simeq -1.563\times 10^{-4}\frac{V}{K}\right)$, those of ZT show a same maximum $(ZT)_{max.}=1$, (ii) for $\xi_n = 1$, those of S, ZT, $(ZT)_{Mott}$, VC1, and T_s present the same results: $-1.322\times 10^{-4}\frac{V}{K}$, 0.715, 3.290, $-1.105\times 10^{-4}\frac{V}{K}$, and $1.657\times 10^{-4}\frac{V}{K}$, respectively, and (iii) for $\xi_n \simeq 1.8138$, $(ZT)_{Mott}=1$.

For x=0,

In the degenerate P- $X(x)$ − alloy, for T= **106.37815 K**, one gets:

$N(10^{18}cm^{-3})$	↘	2.34185		**2.3039912**		2.2678		**1.8777293**	1.876614
ξ_n	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322**	↗ − 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$		−6.524	↗	**0**	↗	6.691	↗	117.542	↗ 117.979
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\,(10^{-3}V)$		−16.6163	↘	−16.6269	↗	−16.6163	↗	−14.0600	↗ −14.0419

In the degenerate As- $X(x)$ − alloy, for T= **121.20698 K**, one gets:

$N(10^{18}cm^{-3})$	↘	2.8482		**2.8021636**		2.75814		**2.283735**	2.28238
ξ_n	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322**	↗ − 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$		−7.433	↗	**0**	↗	7.625	↗	133.927	↗ 134.424
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\,(10^{-3}V)$		−18.9325	↘	−18.9446	↗	−18.9325	↗	−16.0199	↗ −15.9993

In the degenerate Sb- $X(x)$ − alloy, for T= **205.86668 K**, one gets:

$N(10^{18}cm^{-3})$	↘	6.3046		**6.2027052**		6.10524		**5.055142**	5.05214
ξ_n	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322**	↗ − 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$		−12.623	↗	**0**	↗	12.953	↗	227.471	↗ 228.317
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\,(10^{-3}V)$		−32.1564	↘	−32.1769	↗	−32.1564	↗	−27.2094	↗ −27.1744

In the degenerate Sn- $X(x)$ – alloy, for T=**235.65813 K**, one gets:

$N(10^{18}cm^{-3})$	↘	7.7215	**7.5967124**		7.47734		**6.1912438**		6.18757
ξ_n	↘	1.880	**1.8138**		1.750		**1**		0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322**	↗ − 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$		−14.449	↗	**0**	↗	14.827	↗	260.389	↗ 261.356
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\ (10^{-3}V)$		−36.8098	↘	−36.8333	↗	−36.8098	↗	−31.1470	↗ −31.1069

For x=0.5,

In the degenerate P- $X(x)$ – alloy, for T=**68.50458 K**, one gets:

$N(10^{17}cm^{-3})$	↘	7.7213	**7.5964624**		7.4771		**6.1910401**		6.18737
ξ_n	↘	1.880	**1.8138**		1.750		**1**		0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322**	↗ − 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$		−4.202	↗	**0**	↗	4.310	↗	75.694	↗ 75.974
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\ (10^{-3}V)$		−10.7004	↘	−10.7072	↗	−10.7004	↗	−9.0543	↗ −9.0426

In the degenerate As- $X(x)$ – alloy, for T= **78.05392 K**, one gets:

$N(10^{17}cm^{-3})$	↘	9.39081	**9.2389806**		9.09381		**7.5296759**		7.525203
ξ_n	↘	1.880	**1.8138**		1.750		**1**		0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322**	↗ − 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$		−4.788	↗	**0**	↗	4.910	↗	86.245	↗ 86.566
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\ (10^{-3}V)$		−12.1920	↘	−12.1998	↗	−12.1920	↗	−10.3164	↗ −10.3031

In the degenerate Sb- $X(x)$ – alloy, for T=**132.57241 K**, one gets:

$N(10^{18}cm^{-3})$	↘	2.078695	**2.0450866**		2.01296		**1.6667249**		1.665735
ξ_n	↘	1.880	**1.8138**		1.750		**1**		0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322**	↗ − 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$		−8.132	↗	**0**	↗	8.339	↗	146.485	↗ 147.029
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\ (10^{-3}V)$		−20.7078	↘	−20.7210	↗	−20.7078	↗	−17.5221	↗ −17.4996

In the degenerate Sn- $X(x)$ – alloy, for T=**151.757275 K** one gets:

$N(10^{15}cm^{-2})$	↘	2.54586		**2.5047032**		2.465346		**2.0413078**	2.040096
ξ_n	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322**	↗ − 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$		−9.308	↗	**0**	↗	9.548	↗	167.683	↗ 168.306
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\,(10^{-3}V)$		−23.7045	↘	−23.7196	↗	−23.7045	↗	−20.0578	↗ −20.0320

For x=1,

In the degenerate P- $X(x)$ – alloy, for T=**39.091072 K**, one gets:

$N(10^{17}cm^{-2})$	↘	1.74696		**1.7187174**		1.69172		**1.40073732**	1.399906
ξ_n	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322**	↗ − 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$		−2.398	↗	**0**	↗	2.458	↗	43.193	↗ 43.353
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\,(10^{-3}V)$		−6.1060	↘	−6.1099	↗	−6.1060	↗	−5.1667	↗ −5.1600

In the degenerate As- $X(x)$ – alloy, for T=**44.540254 K**, one gets:

$N(10^{17}cm^{-2})$	↘	2.124693		**2.090341**		2.0575		**1.7036068**	1.702595
ξ_n	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322**	↗ − 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$		−2.732	↗	**0**	↗	2.802	↗	49.214	↗ 49.397
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\,(10^{-3}V)$		−6.9572	↘	−6.9616	↗	−6.9572	↗	−5.8869	↗ −5.8793

In the degenerate Sb- $X(x)$ – alloy, for T=**75.650383 K**, one gets:

$N(10^{17}cm^{-2})$	↘	4.703096		**4.6270566**		4.55435		**3.7710043**	3.76877
ξ_n	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322**	↗ − 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mptt}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$		−4.640	↗	**0**	↗	4.759	↗	83.589	↗ 83.899
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\,(10^{-3}V)$		−11.8166	↘	−11.8241	↗	−11.8166	↗	−9.9987	↗ −9.9859

In the degenerate Sn- $X(x)$ – alloy, for T=**86.597926 K**, one gets:

$N(10^{17}cm^{-2})$	↘	5.76008		**5.6669496**		5.5779		**4.61850656**	4.615763
ξ_n	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322**	↗ − 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mott}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$		−5.312	↗	**0**	↗	5.448	↗	95.686	↗ 96.041
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\ (10^{-3}V)$		−13.5266	↘	−13.5352	↗	−13.5266	↗	−11.4457	↗ −11.4309

In the $Y(x) \equiv CdS_{1-x}Se_x - alloy$, for a given T and with decreasing N, the reduced Fermi-energy ξ_n decreases, and other thermoelectric coefficients are in variations, as indicated by the arrows as: (increase: ↗, decrease: ↘). One notes here that with increasing T: (i) for $\xi_n \simeq 1.8138$, while the numerical results of S present a same minimum $(S)_{min.}\left(\simeq -1.563\times 10^{-4}\frac{V}{K}\right)$, those of ZT show a same maximum $(ZT)_{max.} = 1$, (ii) for $\xi_n = 1$, those of S, ZT, $(ZT)_{Mott}$, VC1, and T_s present the same results: $-1.322\times 10^{-4}\frac{V}{K}$, 0.715, 3.290, $-1.105\times 10^{-4}\frac{V}{K}$, and $1.657\times 10^{-4}\frac{V}{K}$, respectively, and (iii) for $\xi_n \simeq 1.8138$, $(ZT)_{Mott} = 1$.

For x=0,

In the degenerate P- $Y(x)$ – alloy, for T= **106.37815 K**, one gets:

$N(10^{18}cm^{-2})$	↘	2.34185		**2.3039912**		2.2678		**1.8777293**	1.876614
ξ_n	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322**	↗ − 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mott}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$		−6.524	↗	**0**	↗	6.691	↗	117.542	↗ 117.979
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\ (10^{-3}V)$		−16.6163	↘	−16.6269	↗	−16.6163	↗	−14.0600	↗ −14.0419

In the degenerate As- $Y(x)$ – alloy, for T= **121.20698 K**, one gets:

$N(10^{18}cm^{-2})$	↘	2.8482		**2.8021636**		2.75814		**2.283735**	2.28238
ξ_n	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322**	↗ − 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mott}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$		−7.433	↗	**0**	↗	7.625	↗	133.927	↗ 134.424
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\ (10^{-3}V)$		−18.9325	↘	−18.9446	↗	−18.9325	↗	−16.0199	↗ −15.9993

In the degenerate Sb- $Y(x)$ – alloy, for T= **205.86668 K**, one gets:

$N(10^{18}cm^{-2})$	↘	6.3046		**6.2027052**		6.10524		**5.055142**	5.05214
ξ_n	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322**	↗ − 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mott}$	↗	0.931		**1**		1.074		**3.290**	3.306

$VC1\left(10^{-4}\frac{V}{K}\right)$	−0.061 ↗	0 ↗	0.063 ↗	**1.105** ↗	1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$	−12.623 ↗	0 ↗	12.953 ↗	227.471 ↗	228.317
$T_s\left(10^{-4}\frac{V}{K}\right)$	−0.092 ↗	0 ↗	0.094 ↗	**1.657** ↗	1.663
$Pt\,(10^{-3}V)$	−32.1564 ↘	−32.1769 ↗	−32.1564 ↗	−27.2094 ↗	−27.1744

In the degenerate Sn- $Y(x)$ – alloy, for T=**235.65813 K**, one gets:

$N(10^{15}cm^{-2})$ ↘	7.7215	**7.5967124**	7.47734	**6.1912438**	6.18757
ξ_n ↘	1.880	**1.8138**	1.750	**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$	−1.562 ↘	**−1.563** ↗	−1.562 ↗	**− 1.322** ↗	− 1.320
ZT	0.999 ↗	**1** ↘	0.999 ↘	**0.715** ↘	0.713
$(ZT)_{Mptt}$ ↗	0.931	**1**	1.074	**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$	−0.061 ↗	0 ↗	0.063 ↗	**1.105** ↗	1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$	−14.449 ↗	0 ↗	14.827 ↗	260.389 ↗	261.356
$T_s\left(10^{-4}\frac{V}{K}\right)$	−0.092 ↗	0 ↗	0.094 ↗	**1.657** ↗	1.663
$Pt\,(10^{-3}V)$	−36.8098 ↘	−36.8333 ↗	−36.8098 ↗	−31.1470 ↗	−31.1069

For x=0.5,

In the degenerate P- $Y(x)$ – alloy, for T=**72.851285 K**, one gets:

$N(10^{17}cm^{-2})$ ↘	9.12852	**8.9809256**	8.8398	**7.3193636**	7.315018
ξ_n ↘	1.880	**1.8138**	1.750	**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$	−1.562 ↘	**−1.563** ↗	−1.562 ↗	**− 1.322** ↗	− 1.320
ZT	0.999 ↗	**1** ↘	0.999 ↘	**0.715** ↘	0.713
$(ZT)_{Mptt}$ ↗	0.931	**1**	1.074	**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$	−0.061 ↗	0 ↗	0.063 ↗	**1.105** ↗	1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$	−4.469 ↗	0 ↗	4.584 ↗	80.497 ↗	80.795
$T_s\left(10^{-4}\frac{V}{K}\right)$	−0.092 ↗	0 ↗	0.094 ↗	**1.657** ↗	1.663
$Pt\,(10^{-3}V)$	−11.3794 ↘	−11.3866 ↗	−11.3794 ↗	−9.6288 ↗	−9.6164

In the degenerate As- $Y(x)$ – alloy, for T= **83.006543 K**, one gets:

$N(10^{15}cm^{-2})$ ↘	1.11023	**1.0922795**	1.07512	**0.8901967**	0.889668
ξ_n ↘	1.880	**1.8138**	1.750	**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$	−1.562 ↘	**−1.563** ↗	−1.562 ↗	**− 1.322** ↗	− 1.320
ZT	0.999 ↗	**1** ↘	0.999 ↘	**0.715** ↘	0.713
$(ZT)_{Mptt}$ ↗	0.931	**1**	1.074	**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$	−0.061 ↗	0 ↗	0.063 ↗	**1.105** ↗	1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$	−5.092 ↗	0 ↗	5.221 ↗	91.718 ↗	92.058
$T_s\left(10^{-4}\frac{V}{K}\right)$	−0.092 ↗	0 ↗	0.094 ↗	**1.657** ↗	1.663
$Pt\,(10^{-3}V)$	−12.9656 ↘	−12.9739 ↗	−12.9656 ↗	−10.9710 ↗	−10.9568

In the degenerate Sb- $Y(x)$ – alloy, for T=**140.984303 K**, one gets:

$N(10^{15}cm^{-2})$ ↘	2.45754	**2.4178058**	2.37982	**1.9704873**	1.969316
ξ_n ↘	1.880	**1.8138**	1.750	**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$	−1.562 ↘	**−1.563** ↗	−1.562 ↗	**− 1.322** ↗	− 1.320
ZT	0.999 ↗	**1** ↘	0.999 ↘	**0.715** ↘	0.713
$(ZT)_{Mptt}$ ↗	0.931	**1**	1.074	**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$	−0.061 ↗	0 ↗	0.063 ↗	**1.105** ↗	1.109

$VC2\left(10^{-4}\frac{V}{K}\right)$	−8.648	↗	**0**	↗	8.869	↗	155.780	↗	156.359
$T_s\left(10^{-4}\frac{V}{K}\right)$	−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗	1.663
$Pt\ (10^{-3}V)$	−22.0217	↘	−22.0358	↗	−22.0217	↗	−18.6339	↗	−18.6099

In the degenerate Sn- $Y(x)$ – alloy, for T=**161.386476 K** one gets:

$N(10^{15}cm^{-2})$	↘	3.009851	**2.961188**		2.91466	**2.4133383**		2.411905	
ξ_n	↘	1.880	**1.8138**		1.750	**1**		0.998	
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562 ↘	**−1.563**	↗	−1.562 ↗	**− 1.322**	↗	− 1.320	
ZT		0.999 ↗	**1**	↘	0.999 ↘	**0.715**	↘	0.713	
$(ZT)_{Mptt}$	↗	0.931	**1**		1.074	**3.290**		3.306	
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061 ↗	**0**	↗	0.063 ↗	**1.105**	↗	1.109	
$VC2\left(10^{-4}\frac{V}{K}\right)$		−9.899 ↗	**0**	↗	**10.154** ↗	178.323	↗	178.986	
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092 ↗	**0**	↗	0.094 ↗	**1.657**	↗	1.663	
$Pt\ (10^{-3}V)$		−25.2086 ↘	−25.2247	↗	−25.2086 ↗	−21.3305	↗	−21.3030	

For x=1,

In the degenerate P- $Y(x)$ – alloy, for T=**46.24488 K**, one gets:

$N(10^{17}cm^{-2})$	↘	2.800698	**2.7554162**		2.71214	**2.24563635**		2.2443023	
ξ_n	↘	1.880	**1.8138**		1.750	**1**		0.998	
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562 ↘	**−1.563**	↗	−1.562 ↗	**− 1.322**	↗	− 1.320	
ZT		0.999 ↗	**1**	↘	0.999 ↘	**0.715**	↘	0.713	
$(ZT)_{Mptt}$	↗	0.931	**1**		1.074	**3.290**		3.306	
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061 ↗	**0**	↗	0.063 ↗	**1.105**	↗	1.109	
$VC2\left(10^{-4}\frac{V}{K}\right)$		−2.837 ↗	**0**	↗	2.908 ↗	51.098	↗	51.288	
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092 ↗	**0**	↗	0.094 ↗	**1.657**	↗	1.663	
$Pt\ (10^{-3}V)$		−7.2234 ↘	−7.2281	↗	−7.2234 ↗	−6.1122	↗	−6.1043	

In the degenerate As- $Y(x)$ – alloy, for T=**52.69128 K**, one gets:

$N(10^{17}cm^{-2})$	↘	3.40627	**3.3511962**		3.29854	**2.731191**		2.72957	
ξ_n	↘	1.880	**1.8138**		1.750	**1**		0.998	
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562 ↘	**−1.563**	↗	−1.562 ↗	**− 1.322**	↗	− 1.320	
ZT		0.999 ↗	**1**	↘	0.999 ↘	**0.715**	↘	0.713	
$(ZT)_{Mptt}$	↗	0.931	**1**		1.074	**3.290**		3.306	
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061 ↗	**0**	↗	0.063 ↗	**1.105**	↗	1.109	
$VC2\left(10^{-4}\frac{V}{K}\right)$		−3.232 ↗	**0**	↗	3.315 ↗	58.221	↗	58.437	
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092 ↗	**0**	↗	0.094 ↗	**1.657**	↗	1.663	
$Pt\ (10^{-3}V)$		−8.2304 ↘	−8.2356	↗	−8.2304 ↗	−6.9642	↗	−6.9553	

In the degenerate Sb- $Y(x)$ – alloy, for T=**102.44566 K**, one gets:

$N(10^{17}cm^{-2})$	↘	7.53992	**7.418012**		7.30149	**6.0456048**		6.042014	
ξ_n	↘	1.880	**1.8138**		1.750	**1**		0.998	
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562 ↘	**−1.563**	↗	−1.562 ↗	**− 1.322**	↗	− 1.320	
ZT		0.999 ↗	**1**	↘	0.999 ↘	**0.715**	↘	0.713	
$(ZT)_{Mptt}$	↗	0.931	**1**		1.074	**3.290**		3.306	
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061 ↗	**0**	↗	0.063 ↗	**1.105**	↗	1.109	
$VC2\left(10^{-4}\frac{V}{K}\right)$		−5.490 ↗	**0**	↗	5.629 ↗	98.887	↗	99.254	

$T_s\left(10^{-4}\frac{V}{K}\right)$	−0.092	↗	0	↗	0.094	↗	**1.657**	↗	1.663
$Pt\,(10^{-3}V)$	−13.9791	↘	−13.9880	↗	−13.9791	↗	−11.8285	↗	−11.8133

In the degenerate Sn- $Y(x)$ – alloy, for T=**102.44566 K**, one gets:

$N(10^{17}cm^{-2})$	↘	9.23445		**9.0851494**		8.9424		**7.404305**	7.399909
ξ_n	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**− 1.322**	↗ − 1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mott}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\left(10^{-4}\frac{V}{K}\right)$		−6.284	↗	**0**	↗	6.445	↗	113.197	↗ 113.617
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\,(10^{-3}V)$		−16.0020	↘	−16.0122	↗	−16.0020	↗	−13.5403	↗ −13.5228

Table 6p

In the $X(x) \equiv CdS_{1-x}Te_x$**-crystalline alloy**, for a given T and with decreasing N, the reduced Fermi-energy ξ_p decreases, and other thermoelectric coefficients are in variations, as indicated by the arrows as: (increase: ↗, decrease: ↘). One notes here that with increasing T: (i) for $\xi_p \simeq 1.8138$, while the numerical results of S present a same minimum $(S)_{min.}\left(\simeq -1.563\times10^{-4}\frac{V}{K}\right)$, those of ZT show a same maximum $(ZT)_{max.}=1$, (ii) for $\xi_p=1$, those of S, ZT, $(ZT)_{Mott}$, VC1, and T_s present the same results: $-1.322\times10^{-4}\frac{V}{K}$, 0.715, 3.290, $-1.105\times10^{-4}\frac{V}{K}$, and $1.657\times10^{-4}\frac{V}{K}$, respectively, and (iii) for $\xi_p \simeq 1.8138$, $(ZT)_{Mott}=1$.

For x=0,

In the degenerate Ga- $X(x)$ – alloy, for T=**342.0192 K**, one gets:

$N(10^{20}cm^{-2})$	↘	1.10689		**1.0889983**		1.071886		**0.8875226**	0.887
ξ_p	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗ −1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mott}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\,(10^{-2}V)$		−0.210	↗	**0**	↗	0.215	↗	3.779	↗ 3.793
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\,(10^{-2}V)$		−5.3423	↘	−5.3457	↗	−5.3423	↗	−4.5205	↗ −4.5147

In the degenerate Mg- $X(x)$ – alloy, for T= **408.85281** K, one gets:

$N(10^{20}cm^{-2})$	↘	1.4467		**1.4233181**		1.40096		**1.1599898**	1.159301
ξ_p	↘	1.880		**1.8138**		1.750		**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗ −1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘ 0.713
$(ZT)_{Mott}$	↗	0.931		**1**		1.074		**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗ 1.109
$VC2\,(10^{-2}V)$		−0.251	↗	**0**	↗	0.257	↗	4.517	↗ 4.534
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗ 1.663
$Pt\,(10^{-2}V)$		−6.3863	↘	−6.3904	↗	−6.3863	↗	−5.4038	↗ −5.3968

In the degenerate In- $X(x)$ – alloy, for T=**416.87247 K**, one gets:

$N(10^{20}cm^{-3})\searrow$	1.48948	**1.4654004**	1.44239	**1.1942865**	1.19358
$\xi_p\quad\searrow$	1.880	**1.8138**	1.750	**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$	−1.562 ↘	**−1.563** ↗	−1.562 ↗	**−1.322** ↗	−1.320
ZT	0.999 ↗	**1** ↘	0.999 ↘	**0.715** ↘	0.713
$(ZT)_{Mptt}\quad\nearrow$	0.931	**1**	1.074	**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$	−0.061 ↗	**0** ↗	0.063 ↗	**1.105** ↗	1.109
$VC2(10^{-2}V)$	−0.256 ↗	**0** ↗	0.262 ↗	4.606 ↗	4.623
$T_s\left(10^{-4}\frac{V}{K}\right)$	−0.092 ↗	**0** ↗	0.094 ↗	**1.657** ↗	1.663
$Pt\,(10^{-2}V)$	−6.5115 ↘	−6.5157 ↗	−6.5115 ↗	−5.5098 ↗	−5.5027

In the degenerate Cd- $X(x)$ – alloy, for T=**419.59401 K**, one gets:

$N(10^{20}cm^{-3})\searrow$	1.504093	**1.479774**	1.45652	**1.2060009**	1.205284
$\xi_p\quad\searrow$	1.880	**1.8138**	1.750	**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$	−1.562 ↘	**−1.563** ↗	−1.562 ↗	**−1.322** ↗	−1.320
ZT	0.999 ↗	**1** ↘	0.999 ↘	**0.715** ↘	0.713
$(ZT)_{Mptt}\quad\nearrow$	0.931	**1**	1.074	**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$	−0.061 ↗	**0** ↗	0.063 ↗	**1.105** ↗	1.109
$VC2(10^{-2}V)$	−0.257 ↗	**0** ↗	0.264 ↗	4.636 ↗	4.653
$T_s\left(10^{-4}\frac{V}{K}\right)$	−0.092 ↗	**0** ↗	0.094 ↗	**1.657** ↗	1.663
$Pt\,(10^{-2}V)$	−6.5540 ↘	−6.5582 ↗	−6.5540 ↗	−5.5458 ↗	−5.5386

For x=0.5,

In the degenerate Ga- $X(x)$ – alloy, for T=**300.71248** K, one gets:

$N(10^{20}cm^{-3})\searrow$	9.2883	**9.1381736**	8.99459	**7.447519**	7.443095
$\xi_p\quad\searrow$	1.880	**1.8138**	1.750	**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$	−1.562 ↘	**−1.563** ↗	−1.562 ↗	**−1.322** ↗	−1.320
ZT	0.999 ↗	**1** ↘	0.999 ↘	**0.715** ↘	0.713
$(ZT)_{Mptt}\quad\nearrow$	0.931	**1**	1.074	**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$	−0.061 ↗	**0** ↗	0.063 ↗	**1.105** ↗	1.109
$VC2(10^{-2}V)$	−0.184 ↗	**0** ↗	0.189 ↗	3.323 ↗	3.335
$T_s\left(10^{-4}\frac{V}{K}\right)$	−0.092 ↗	**0** ↗	0.094 ↗	**1.657** ↗	1.663
$Pt\,(10^{-2}V)$	−4.6971 ↘	−4.7001 ↗	−4.6971 ↗	−3.9745 ↗	−3.9694

In the degenerate Mg- $X(x)$ – alloy, for **T=359.47439 K**, one gets:

$N(10^{20}cm^{-3})\searrow$	1.213985	**1.194357**	1.175589	**0.9733889**	0.972811
$\xi_p\quad\searrow$	1.880	**1.8138**	1.750	**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$	−1.562 ↘	**−1.563** ↗	−1.562 ↗	**−1.322** ↗	−1.320
ZT	0.999 ↗	**1** ↘	0.999 ↘	**0.715** ↘	0.713
$(ZT)_{Mptt}\quad\nearrow$	0.931	**1**	1.074	**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$	−0.061 ↗	**0** ↗	0.063 ↗	**1.105** ↗	1.109
$VC2(10^{-2}V)$	−0.220 ↗	**0** ↗	0.226 ↗	3.972 ↗	3.986
$T_s\left(10^{-4}\frac{V}{K}\right)$	−0.092 ↗	**0** ↗	0.094 ↗	**1.657** ↗	1.663
$Pt\,(10^{-2}V)$	−5.6150 ↘	−5.6186 ↗	−5.6150 ↗	−4.7512 ↗	−4.7451

In the degenerate In- $X(x)$ – alloy, for T=**366.52549 K**, one gets:

$N(10^{20}cm^{-3})\searrow$	1.249877	**1.2296698**	1.21035	**1.0021685**	1.001574

ξ_p	↘	1.880	**1.8138**	1.750	**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗	−1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘	0.713
$(ZT)_{Mptt}$	↗	0.931	**1**	1.074	**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	0	↗	0.063	↗	**1.105**	↗	1.109
$VC2(10^{-2}V)$		−0.225	↗	0	↗	0.230	↗	4.050	↗	4.064
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	0	↗	0.094	↗	**1.657**	↗	1.663
$Pt\,(10^{-2}V)$		−5.7251	↘	−5.7288	↗	−5.7251	↗	−4.8444	↗	−4.8381

In the degenerate Cd- $X(x)$ – alloy, for T=**368.91834 K**, one gets:

$N(10^{20}cm^{-2})$	↘	1.262136	**1.2417312**	1.22222	**1.0119984**	1.011398
ξ_p	↘	1.880	**1.8138**	1.750	**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗	−1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘	0.713
$(ZT)_{Mptt}$	↗	0.931	**1**	1.074	**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	0	↗	0.063	↗	**1.105**	↗	1.109
$VC2(10^{-2}V)$		−0.226	↗	0	↗	0.232	↗	4.076	↗	4.091
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	0	↗	0.094	↗	**1.657**	↗	1.663
$Pt\,(10^{-2}V)$		−5.7625	↘	−5.7662	↗	−5.7625	↗	−4.8760	↗	−4.8697

For x=1,

In the degenerate Ga- $X(x)$ – alloy, for T=**266.80841** K, one gets:

$N(10^{19}cm^{-2})$	↘	7.89954	**7.7718202**	7.6497	**6.333955**	6.33019
ξ_p	↘	1.880	**1.8138**	1.750	**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗	−1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘	0.713
$(ZT)_{Mptt}$	↗	0.931	**1**	1.074	**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	0	↗	0.063	↗	**1.105**	↗	1.109
$VC2(10^{-2}V)$		−0.164	↗	0	↗	0.168	↗	2.948	↗	2.959
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	0	↗	0.094	↗	**1.657**	↗	1.663
$Pt\,(10^{-2}V)$		−4.1675	↘	−4.1702	↗	−4.1675	↗	−3.5264	↗	−3.5219

In the degenerate Mg- $X(x)$ – alloy, for T=**318.94516** K, one gets:

$N(10^{20}cm^{-2})$	↘	1.03246	**1.015775**	0.999813	**0.8278463**	0.827355
ξ_p	↘	1.880	**1.8138**	1.750	**1**	0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗	−1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘	0.713
$(ZT)_{Mptt}$	↗	0.931	**1**	1.074	**3.290**	3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	0	↗	0.063	↗	**1.105**	↗	1.109
$VC2(10^{-2}V)$		−0.195	↗	0	↗	0.201	↗	3.524	↗	3.537
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	0	↗	0.094	↗	**1.657**	↗	1.663
$Pt\,(10^{-2}V)$		−4.9819	↘	−4.9851	↗	−4.9819	↗	−4.2155	↗	−4.2101

In the degenerate In- $X(x)$ – alloy, for T=**325.20128** K, one gets:

$N(10^{20}cm^{-2})$	↘	1.062994	**1.0458077**	1.02938	**0.8523227**	0.85182
ξ_p	↘	1.880	**1.8138**	1.750	**1**	0.998

$S\left(10^{-4}\frac{V}{K}\right)$	−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗	−1.320
ZT	0.999	↗	**1**	↘	0.999	↘	**0.715**	↘	0.713
$(ZT)_{Mptt}$	0.931	↗	**1**		1.074		**3.290**		3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$	−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗	1.109
$VC2(10^{-2}V)$	−0.199	↗	**0**	↗	0.204	↗	3.593	↗	3.606
$T_s\left(10^{-4}\frac{V}{K}\right)$	−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗	1.663
$Pt\,(10^{-2}V)$	−5.0796	↘	−5.0829	↗	−5.0796	↗	−4.2982	↗	−4.2927

In the degenerate Cd- $X(x)-$ alloy, for T=**327.32434** K, one gets:

$N(10^{20}cm^{-3})$	1.07342	↘	**1.0560657**		1.039471		**0.86068286**		0.860173
ξ_p	1.880	↘	**1.8138**		1.750		**1**		0.998
$S\left(10^{-4}\frac{V}{K}\right)$	−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗	−1.320
ZT	0.999	↗	**1**	↘	0.999	↘	**0.715**	↘	0.713
$(ZT)_{Mptt}$	0.931	↗	**1**		1.074		**3.290**		3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$	−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗	1.109
$VC2(10^{-2}V)$	−0.201	↗	**0**	↗	0.206	↗	3.617	↗	3.630
$T_s\left(10^{-4}\frac{V}{K}\right)$	−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗	1.663
$Pt\,(10^{-2}V)$	−5.1128	↘	−5.1161	↗	−5.1128	↗	−4.3262	↗	−4.3207

In the $\mathbf{Y(x) \equiv CdS_{1-x}Se_x - alloy}$, for a given T and with decreasing N, the reduced Fermi-energy ξ_p decreases, and other thermoelectric coefficients are in variations, as indicated by the arrows as: (increase: ↗, decrease: ↘). One notes here that with increasing T: (i) for $\xi_p \simeq 1.8138$, while the numerical results of S present a same minimum $(S)_{min.}\left(\simeq -1.563\times 10^{-4}\frac{V}{K}\right)$, those of ZT show a same maximum $(ZT)_{max.}=1$, (ii) for $\xi_p=1$, those of S, ZT, $(ZT)_{Mott}$, VC1, and T_s present the same results: $-1.322\times 10^{-4}\frac{V}{K}$, 0.715, 3.290, $-1.105\times 10^{-4}\frac{V}{K}$, and $1.657\times 10^{-4}\frac{V}{K}$, respectively, and (iii) for $\xi_p \simeq 1.8138$, $(ZT)_{Mott}=1$.

For x=0,

In the degenerate Ga- $Y(x)-$ alloy, for T=**342.0192 K**, one gets:

$N(10^{20}cm^{-3})$	1.10689	↘	**1.0889983**		1.071886		**0.8875226**		0.887
ξ_p	1.880	↘	**1.8138**		1.750		**1**		0.998
$S\left(10^{-4}\frac{V}{K}\right)$	−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗	−1.320
ZT	0.999	↗	**1**	↘	0.999	↘	**0.715**	↘	0.713
$(ZT)_{Mptt}$	0.931	↗	**1**		1.074		**3.290**		3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$	−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗	1.109
$VC2(10^{-2}V)$	−0.210	↗	**0**	↗	0.215	↗	3.779	↗	3.793
$T_s\left(10^{-4}\frac{V}{K}\right)$	−0.092	↗	**0**	↗	0.094	↗	**1.657**	↗	1.663
$Pt\,(10^{-2}V)$	−5.3423	↘	−5.3457	↗	−5.3423	↗	−4.5205	↗	−4.5147

In the degenerate Mg- $Y(x)-$ alloy, for T= **408.85281** K, one gets:

$N(10^{20}cm^{-3})$	1.4467	↘	**1.4233181**		1.40096		**1.1599898**		1.159301
ξ_p	1.880	↘	**1.8138**		1.750		**1**		0.998
$S\left(10^{-4}\frac{V}{K}\right)$	−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗	−1.320
ZT	0.999	↗	**1**	↘	0.999	↘	**0.715**	↘	0.713
$(ZT)_{Mptt}$	0.931	↗	**1**		1.074		**3.290**		3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$	−0.061	↗	**0**	↗	0.063	↗	**1.105**	↗	1.109
$VC2(10^{-2}V)$	−0.251	↗	**0**	↗	0.257	↗	4.517	↗	4.534

$T_s\left(10^{-4}\frac{V}{K}\right)$	−0.092	↗	0	↗	0.094	↗	**1.657**	↗	1.663
$Pt\,(10^{-2}V)$	−6.3863	↘	−6.3904	↗	−6.3863	↗	−5.4038	↗	−5.3968

In the degenerate In- $Y(x)$ – alloy, for T=**416.87247 K**, one gets:

$N(10^{20}cm^{-3})$	1.48948	↘	**1.4654004**		1.44239		**1.1942865**		1.19358
ξ_p	1.880	↘	**1.8138**		1.750		**1**		0.998
$S\left(10^{-4}\frac{V}{K}\right)$	−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗	−1.320
ZT	0.999	↗	**1**	↘	0.999	↘	**0.715**	↘	0.713
$(ZT)_{Mott}$	0.931	↗	**1**		1.074		**3.290**		3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$	−0.061	↗	0	↗	0.063	↗	**1.105**	↗	1.109
$VC2\,(10^{-2}V)$	−0.256	↗	0	↗	0.262	↗	4.606	↗	4.623
$T_s\left(10^{-4}\frac{V}{K}\right)$	−0.092	↗	0	↗	0.094	↗	**1.657**	↗	1.663
$Pt\,(10^{-2}V)$	−6.5115	↘	−6.5157	↗	−6.5115	↗	−5.5098	↗	−5.5027

In the degenerate Cd- $Y(x)$ – alloy, for T=**419.59401 K**, one gets:

$N(10^{20}cm^{-3})$	1.504093	↘	**1.479774**		1.45652		**1.2060009**		1.205284
ξ_p	1.880	↘	**1.8138**		1.750		**1**		0.998
$S\left(10^{-4}\frac{V}{K}\right)$	−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗	−1.320
ZT	0.999	↗	**1**	↘	0.999	↘	**0.715**	↘	0.713
$(ZT)_{Mott}$	0.931	↗	**1**		1.074		**3.290**		3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$	−0.061	↗	0	↗	0.063	↗	**1.105**	↗	1.109
$VC2\,(10^{-2}V)$	−0.257	↗	0	↗	0.264	↗	4.636	↗	4.653
$T_s\left(10^{-4}\frac{V}{K}\right)$	−0.092	↗	0	↗	0.094	↗	**1.657**	↗	1.663
$Pt\,(10^{-2}V)$	−6.5540	↘	−6.5582	↗	−6.5540	↗	−5.5458	↗	−5.5386

For x=0.5,

In the degenerate Ga- $Y(x)$ – alloy, for T=**234.74039** K, one gets:

$N(10^{19}cm^{-3})$	4.343145	↘	**4.2729264**		4.20578		**3.4823918**		3.48033
ξ_p	1.880	↘	**1.8138**		1.750		**1**		0.998
$S\left(10^{-4}\frac{V}{K}\right)$	−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗	−1.320
ZT	0.999	↗	**1**	↘	0.999	↘	**0.715**	↘	0.713
$(ZT)_{Mott}$	0.931	↗	**1**		1.074		**3.290**		3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$	−0.061	↗	0	↗	0.063	↗	**1.105**	↗	1.109
$VC2\,(10^{-2}V)$	−0.144	↗	0	↗	0.148	↗	2.594	↗	2.603
$T_s\left(10^{-4}\frac{V}{K}\right)$	−0.092	↗	0	↗	0.094	↗	**1.657**	↗	1.663
$Pt\,(10^{-2}V)$	−3.6666	↘	−3.6690	↗	−3.6666	↗	−3.1026	↗	−3.0986

In the degenerate Mg- $Y(x)$ – alloy, for **T=280.61078 K**, one gets:

$N(10^{19}cm^{-3})$	5.67648	↘	**5.5847044**		5.49695		**4.5514777**		4.54878
ξ_p	1.880	↘	**1.8138**		1.750		**1**		0.998
$S\left(10^{-4}\frac{V}{K}\right)$	−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗	−1.320
ZT	0.999	↗	**1**	↘	0.999	↘	**0.715**	↘	0.713
$(ZT)_{Mott}$	0.931	↗	**1**		1.074		**3.290**		3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$	−0.061	↗	0	↗	0.063	↗	**1.105**	↗	1.109
$VC2\,(10^{-2}V)$	−0.172	↗	0	↗	0.176	↗	3.100	↗	3.112

$T_s\left(10^{-4}\frac{V}{K}\right)$	−0.092	↗	0	↗	0.094	↗	**1.657**	↗	1.663
$Pt\,(10^{-2}V)$	−4.3831	↘	−4.3859	↗	−4.3831	↗	−3.7088	↗	−3.7041

In the degenerate In- $Y(x)$ – alloy, for T=**286.11496 K**, one gets:

$N(10^{19}cm^{-2})$	↘	5.84431	**5.7498236**		5.65948		**4.686048**		4.68327
ξ_p	↘	1.880	**1.8138**		1.750		**1**		0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘ **−1.563**	↗	−1.562	↗	**−1.322**	↗	−1.320
ZT		0.999	↗ **1**	↘	0.999	↘	**0.715**	↘	0.713
$(ZT)_{Mptt}$	↗	0.931	**1**		1.074		**3.290**		3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗ 0	↗	0.063	↗	**1.105**	↗	1.109
$VC2\,(10^{-2}V)$		−0.175	↗ 0	↗	0.180	↗	3.161	↗	3.173
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗ 0	↗	0.094	↗	**1.657**	↗	1.663
$Pt\,(10^{-2}V)$		−4.4691	↘ −4.4720	↗	−4.4691	↗	−3.7816	↗	−3.7767

In the degenerate Cd- $Y(x)$ – alloy, for T=**287.98285 K**, one gets:

$N(10^{19}cm^{-2})$	↘	5.9016	**5.8062216**		5.715		**4.7320119**		4.72921
ξ_p	↘	1.880	**1.8138**		1.750		**1**		0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘ **−1.563**	↗	−1.562	↗	**−1.322**	↗	−1.320
ZT		0.999	↗ **1**	↘	0.999	↘	**0.715**	↘	0.713
$(ZT)_{Mptt}$	↗	0.931	**1**		1.074		**3.290**		3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗ 0	↗	0.063	↗	**1.105**	↗	1.109
$VC2\,(10^{-2}V)$		−0.176	↗ 0	↗	0.181	↗	3.182	↗	3.194
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗ 0	↗	0.094	↗	**1.657**	↗	1.663
$Pt\,(10^{-2}V)$		−4.4983	↘ −4.5012	↗	−4.4983	↗	−3.8063	↗	−3.8014

For x=1,

In the degenerate Ga- $Y(x)$ – alloy, for T=**149.59434** K, one gets:

$N(10^{19}cm^{-2})$	↘	1.348259	**1.3264601**		1.30562		**1.0810516**		1.08041
ξ_p	↘	1.880	**1.8138**		1.750		**1**		0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘ **−1.563**	↗	−1.562	↗	**−1.322**	↗	−1.320
ZT		0.999	↗ **1**	↘	0.999	↘	**0.715**	↘	0.713
$(ZT)_{Mptt}$	↗	0.931	**1**		1.074		**3.290**		3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗ 0	↗	0.063	↗	**1.105**	↗	1.109
$VC2\,(10^{-2}V)$		−0.092	↗ 0	↗	0.094	↗	1.653	↗	1.659
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗ 0	↗	0.094	↗	**1.657**	↗	1.663
$Pt\,(10^{-2}V)$		−2.3367	↘ −2.3381	↗	−2.3367	↗	−1.9772	↗	−1.9746

In the degenerate Mg- $Y(x)$ – alloy, for T=**178.82641** K, one gets:

$N(10^{19}cm^{-2})$	↘	1.76217	**1.7336801**		1.70644		**1.41293177**		1.412093
ξ_p	↘	1.880	**1.8138**		1.750		**1**		0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘ **−1.563**	↗	−1.562	↗	**−1.322**	↗	−1.320
ZT		0.999	↗ **1**	↘	0.999	↘	**0.715**	↘	0.713
$(ZT)_{Mptt}$	↗	0.931	**1**		1.074		**3.290**		3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗ 0	↗	0.063	↗	**1.105**	↗	1.109
$VC2\,(10^{-2}V)$		−0.110	↗ 0	↗	0.112	↗	1.976	↗	1.983
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗ 0	↗	0.094	↗	**1.657**	↗	1.663

$Pt\,(10^{-2}V)$	−2.7933	↘	−2.7950	↗	−2.7933	↗	−2.3635	↗	−2.3605

In the degenerate In- $Y(x)$ − alloy, for T=**182.3341** K, one gets:

$N(10^{19}cm^{-3})$	↘	1.81427	**1.7849387**		1.7569		**1.454707**		1.453843
ξ_p	↘	1.880	**1.8138**		1.750		**1**		0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗	−1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘	0.713
$(ZT)_{Mptt}$	↗	0.931	**1**		1.074		**3.290**		3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	0	↗	0.063	↗	**1.105**	↗	1.109
$VC2\,(10^{-2}V)$		−0.112	↗	0	↗	0.114	↗	2.014	↗	2.022
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	0	↗	0.094	↗	**1.657**	↗	1.663
$Pt\,(10^{-2}V)$		−2.8480	↘	−2.8500	↗	−2.8480	↗	−2.4099	↗	−2.4068

In the degenerate Cd- $Y(x)$ − alloy, for T=**183.52446** K, one gets:

$N(10^{19}cm^{-3})$	↘	1.83206	**1.8024466**		1.77413		**1.4689757**		1.468104
ξ_p	↘	1.880	**1.8138**		1.750		**1**		0.998
$S\left(10^{-4}\frac{V}{K}\right)$		−1.562	↘	**−1.563**	↗	−1.562	↗	**−1.322**	↗	−1.320
ZT		0.999	↗	**1**	↘	0.999	↘	**0.715**	↘	0.713
$(ZT)_{Mptt}$	↗	0.931	**1**		1.074		**3.290**		3.306
$VC1\left(10^{-4}\frac{V}{K}\right)$		−0.061	↗	0	↗	0.063	↗	**1.105**	↗	1.109
$VC2\,(10^{-2}V)$		−0.112	↗	0	↗	0.115	↗	2.028	↗	2.035
$T_s\left(10^{-4}\frac{V}{K}\right)$		−0.092	↗	0	↗	0.094	↗	**1.657**	↗	1.663
$Pt\,(10^{-2}V)$		−2.8666	↘	−2.8685	↗	−2.8666	↗	−2.4256	↗	−2.4225